
Connect SDK Documentation

Ingram Micro

Jun 05, 2019

Contents

1	Introduction	1
1.1	Installation	2
1.2	Requirements	2
2	Contents	3
2.1	Examples	3
2.2	API Reference	8
3	Indices and tables	29
	Python Module Index	31
	Index	33

Connect Python SDK allows an easy and fast integration with Connect fulfillment API. Thanks to it you can automate the fulfillment of orders generated by your products.

In order to use this library, please ensure that you have read first the documentation available on Connect knowledge base article located [here](#), this one will provide you a great information on the REST API that this library implements.

This library may be consumed in your project in order to automate the fulfillment of requests, this class once imported into your project will allow you to:

- Communicate with Connect using your API credentials.
- **List all requests, and even filter them:**
 - For a specific product.
 - For a specific status.
 - For a specific asset.
 - Etc.
- Process each request and obtain full details of the request.
- **Modify the activation parameters of each request in order to:**
 - Inquiry for changes
 - Store information into the fulfillment request
- Change the status of the requests from its initial pending state to either inquiring, failed or approved.
- Generate and upload usage files to report usage for active contracts and listings.
- Process usage file status changes.
- Work with Notes for requests.
- Generate logs.
- Collect debug logs in case of failure.

Your code may use any scheduler to execute, from a simple cron to a cloud scheduler like the ones available in Azure, Google, Amazon or other cloud platforms.

1.1 Installation

In order to use the SDK with your product, you must install the `connect-sdk` package from [PyPI \(Python Package Index\)](#). You can do so using `pip`:

```
$ pip install connect-sdk
```

1.2 Requirements

- Python 2.7+ or Python 3.4+
- Requests
- Marshmallow

2.1 Examples

2.1.1 Processing Fulfillment Requests

```
# -*- coding: utf-8 -*-  
  
# This file is part of the Ingram Micro Cloud Blue Connect SDK.  
# Copyright (c) 2019 Ingram Micro. All Rights Reserved.  
  
from typing import Union  
import warnings  
  
from connect.config import Config  
from connect.exceptions import FailRequest, InquireRequest, SkipRequest  
from connect.logger import logger  
from connect.models import ActivationTemplateResponse, ActivationTileResponse,  
↳ Fulfillment  
from connect.resources import FulfillmentAutomation  
  
# Enable processing of deprecation warnings  
warnings.simplefilter('default')  
  
# Set logger level / default level ERROR  
logger.setLevel('DEBUG')  
  
# If we remove this line, it is done implicitly  
Config(file='config.json')  
  
class FulfillmentExample(FulfillmentAutomation):  
    def process_request(self, request):  
        # type: (Fulfillment) -> Union[ActivationTemplateResponse,  
↳ ActivationTileResponse]
```

(continues on next page)

```

    if request.needs_migration():
        # Skip request if it needs migration (migration is performed by an
↪external service)
        logger.info('Skipping request {} because it needs migration.'.
↪format(request.id))
        raise SkipRequest()
    else:
        logger.info('Processing request {} for contract {}, product {},
↪marketplace {}'.format(request.id,
                            request.contract.id,
                            request.asset.product.name,
                            request.marketplace.name))

        # Custom logic
        if request.type == 'purchase':
            for item in request.asset.items:
                if item.quantity > 100000:
                    raise FailRequest(
                        message='Is Not possible to purchase product')

            for param in request.asset.params:
                if param.name == 'email' and not param.value:
                    param.value_error = 'Email address has not been provided, ' \
                                        'please provide one'
                    raise InquireRequest(params=[param])

            # Approve by ActivationTile
            return ActivationTileResponse('\n # Welcome to Fallball!\n\nYes, you
↪decided '
                                        'to have an account in our amazing
↪service!')

            # Or
            # return TemplateResource().render(pk='TEMPLATE_ID', request_
↪id=request.id)

            # Approve by Template
            # return ActivationTemplateResponse('TL-497-535-242')
            # Or
            # return TemplateResource().get(pk='TEMPLATE_ID')

        elif request.type == 'change':
            # Fail
            raise FailRequest()
        else:
            # Skip request
            raise SkipRequest()

if __name__ == '__main__':
    fulfillment_example = FulfillmentExample()
    fulfillment_example.process()

```


2.1.2 Processing Tier Config Requests

```
# -*- coding: utf-8 -*-

# This file is part of the Ingram Micro Cloud Blue Connect SDK.
# Copyright (c) 2019 Ingram Micro. All Rights Reserved.

# NOTE: This example development is in progress. This is just a skeleton.

from typing import Union
import warnings

from connect.config import Config
from connect.logger import logger
from connect.models import ActivationTemplateResponse, ActivationTileResponse, \
↳TierConfigRequest
from connect.resources import TierConfigAutomation

# Enable processing of deprecation warnings
warnings.simplefilter('default')

# Set logger level / default level ERROR
logger.setLevel('DEBUG')

# If we remove this line, it is done implicitly
Config(file='config.json')

class TierConfigExample(TierConfigAutomation):
    def process_request(self, request):
        # type: (TierConfigRequest) -> Union[ActivationTemplateResponse, \
↳ActivationTileResponse]
        pass

if __name__ == '__main__':
    tier_config_example = TierConfigExample()
    tier_config_example.process()
```

2.1.3 Reporting Usage Files

```
# -*- coding: utf-8 -*-

# This file is part of the Ingram Micro Cloud Blue Connect SDK.
# Copyright (c) 2019 Ingram Micro. All Rights Reserved.

from datetime import date, timedelta
import time
import warnings

from connect.config import Config
from connect.logger import logger
from connect.models import Contract, UsageRecord, UsageFile, UsageListing, Product
from connect.resources import UsageAutomation
```

(continues on next page)

```

# Enable processing of deprecation warnings
warnings.simplefilter('default')

# Set logger level / default level ERROR
logger.setLevel('DEBUG')

# If we remove this line, it is done implicitly
Config(file='config.json')

class UsageExample(UsageAutomation):
    def process_request(self, request):
        # type: (UsageListing) -> None

        # Detect specific provider contract
        if request.contract.id == 'CRD-41560-05399-123':
            # Can also be seen from request.provider.id and parametrized further
            # via marketplace available at request.marketplace.id
            usage_file = UsageFile(
                name='sdk test',
                product=Product(id=request.product.id),
                contract=Contract(id=request.contract.id)
            )

            usages = [
                UsageRecord(
                    record_id='unique record value',

                    item_search_criteria='item.mpn',
                    # Possible values are item.mpn or item.local_id.

                    item_search_value='SKUA',
                    # Value defined as MPN on vendor portal.

                    quantity=1,
                    # Quantity to be reported.

                    start_time_utc=(date.today() - timedelta(1)).strftime('%Y-%m-%d'),
                    # From when to report.

                    end_time_utc=time.strftime('%Y-%m-%d %H:%M:%S'),
                    # Till when to report.

                    asset_search_criteria='parameter.param_b',
                    # How to find the asset on Connect. Typical use case is to use a
↳parameter
                    # provided by vendor, in this case called param_b. Additionally,
↳asset.id
                    # can be used in case you want to use Connect identifiers.

                    asset_search_value='tenant2'
                )
            ]

            self.submit_usage(usage_file, usages)
        else:
            # Something different could be done here

```

(continues on next page)

(continued from previous page)

```

    pass

if __name__ == '__main__':
    usage_example = UsageExample()
    usage_example.process()

```

2.1.4 Workflow of Usage Files

```

# -*- coding: utf-8 -*-

# This file is part of the Ingram Micro Cloud Blue Connect SDK.
# Copyright (c) 2019 Ingram Micro. All Rights Reserved.

import warnings

from connect.config import Config
from connect.logger import logger
from connect.exceptions import AcceptUsageFile, DeleteUsageFile, SkipRequest, \
    SubmitUsageFile
from connect.models import UsageFile
from connect.resources import UsageFileAutomation

# Enable processing of deprecation warnings
warnings.simplefilter('default')

# Set logger level / default level ERROR
logger.setLevel('DEBUG')

# If we remove this line, it is done implicitly
Config(file='config.json')

class UsageFileExample(UsageFileAutomation):
    def process_request(self, request):
        # type: (UsageFile) -> None
        if request.status == 'invalid':
            # Vendor and provider may handle invalid cases differently,
            # probably notifying their staff
            raise DeleteUsageFile('Not needed anymore')
        elif request.status == 'ready':
            # Vendor may submit file to provider
            raise SubmitUsageFile('Ready for provider')
        elif request.status == 'pending':
            # Provider use case, needs to be reviewed and accepted
            raise AcceptUsageFile('File looks good')
        else:
            raise SkipRequest('Non controlled status')

if __name__ == '__main__':
    usage_file_example = UsageFileExample()
    usage_file_example.process()

```

2.2 API Reference

2.2.1 config

class `connect.config.Config` (*api_url=None, api_key=None, products=None, file=None*)

Initialization config for public api.

Parameters

- **api_url** (*str*) – Public api url.
- **api_key** (*str*) – Service user ApiKey.
- **products** (*str/list[str]*) – Optional product ids.
- **file** (*str*) – Config file name.

Raises

- **ValueError** – Raised if either `file` or one of `api_url` or `api_key` are missing.
- **TypeError** – Raised if `products` is not a string or list of strings, or if config file does not contain JSON data.
- **IOError** – Raised if the specified `file` could not be opened.

`api_key`

Returns ApiKey.

Return type str

`api_url`

Returns Api URL.

Return type str

classmethod `get_instance()`

Returns Global instance.

Return type *Config*

`products`

Returns Valid product ids.

Return type list[str]

2.2.2 exceptions

exception `connect.exceptions.AcceptUsageFile` (*acceptance_note*)

exception `connect.exceptions.CloseUsageFile` (*message=None*)

exception `connect.exceptions.DeleteUsageFile` (*message=None*)

exception `connect.exceptions.FailRequest` (*message=""*)

Causes the request being processed to fail.

Parameters **message** (*str*) – Exception message.

exception `connect.exceptions.FileCreationError` (*message*)

exception `connect.exceptions.FileRetrievalError` (*message*)

exception `connect.exceptions.InquireRequest` (*message=""*, *params=None*)
Causes the request being processed to inquire for some information.

Parameters

- **message** (*str*) – Exception message.
- **params** (*List [Param]*) – Parameters to inquire.

params = None

(*List [Param]*) Parameters to inquire.

exception `connect.exceptions.Message` (*message=""*, *code=""*, *obj=None*)
Base class for all Connect exceptions.

Parameters

- **message** (*str*) – Exception message.
- **code** (*str*) – Exception code.
- **obj** (*object*) – Additional information.

code = None

(*str*) Exception code.

message

Returns The exception message.

Return type *str*

Deprecated since version 16.0: Use `str(exception)` instead.

obj = None

(*str*) Additional information.

exception `connect.exceptions.RejectUsageFile` (*message=None*)

exception `connect.exceptions.ServerError` (*error*)

Indicates that the server returned an error.

Parameters **error** (*ServerErrorResponse*) – Response returned by the server.

exception `connect.exceptions.SkipRequest` (*message=""*)

Causes the request being processed to be skipped.

Parameters **message** (*str*) – Exception message.

exception `connect.exceptions.SubmitUsageFile` (*rejection_note*)

exception `connect.exceptions.UsageFileAction` (*message*, *code*, *data=None*)

Base exception for Usage API actions.

Parameters

- **message** (*str*) – Exception message.
- **code** (*str*) – Exception code.
- **data** (*Optional [Dict [str, Any]]*) – Additional information.

2.2.3 models

class `connect.models.Activation` (***kwargs*)

Activation object.

date = None
(datetime.datetime|None) Activation date.

link = None
(str|None) Activation link.

message = None
(str) Activation message.

class connect.models.**Agreement** (**kwargs)
An Agreement object.

active = None
(bool) State of the version.

agreements = None
(List[*Agreement*]) Program agreements can have distribution agreements associated with them.

author = None
(*User* | None) Reference to the user who created the version.

created = None
(datetime.datetime) Date of creation of the agreement.

description = None
(str) Agreement details (Markdown).

link = None
(str) Url to the document.

marketplace = None
(*Marketplace* | None) Reference to marketplace object (for distribution agreement).

owner = None
(*Company*) Reference to the owner account object.

parent = None
(*Agreement* | None) Reference to the parent program agreement (for distribution agreement).

stats = None
(*AgreementStats* | None) Agreement stats.

title = None
(str) Title of the agreement.

type = None
(str) Type of the agreement. One of: distribution, program, service.

updated = None
(datetime.datetime) Date of the update of the agreement. It can be creation of the new version, change of the field, etc. (any change).

version = None
(int) Chronological number of the version.

version_contracts = None
(int) Number of contracts this version has.

version_created = None
(datetime.datetime) Date of the creation of the version.

class connect.models.**AgreementStats** (**kwargs)
Agreement stats.

contracts = None
(int|None) Number of contracts this agreement has.

versions = None
(int) Number of versions in the agreement.

class `connect.models.Asset` (**kwargs)

Represents a saleable item that can be provided/distributed in terms of one purchase.

These assets can be requested using `connect.resource.FulfillmentAutomation` resource.

An asset is characterized by the following:

- Every asset reflects some purchase (somebody purchases either a service or a good).
- Purchase action can be reverted (canceled) or terminated when terms of purchase are expired, see full state diagram on FIG.5
- Asset can be subscription-based (when customer pay for usage in some time terms) or one-time based.
- Matter of asset is defined as list of purchased items with purchased quantities (asset items).
- Item in asset may be either reservation-based, when customer decides how many items of SKU to be purchased or Pay-Per-User based when actual use of the SKU defines quantity for asset item.
- Asset may be modified using change requests: either set of items may be changed or quantities of reservation-based items may be changed.
- Some assets can be put into suspend state, when service is not actually provided and no charges happened.
- Assets also may be parametrized by one or more parameters which are differentiate one asset from another.

connection = None
(*Connection*) Connection object.

external_id = None
(str) Identification for asset object on eCommerce.

external_uid = None
(str|None) Id of asset in eCommerce system

get_item_by_mpn (mpn)
Get an item of the asset.

Parameters **mpn** (*str*) – MPN of the item to get.

Returns The item with the given MPN, or *None* if it was not found.

Return type *Item* | *None*

get_param_by_id (id_)
Get a parameter of the asset.

Parameters **id** (*str*) – Id of the the parameter to get.

Returns The parameter with the given id, or *None* if it was not found.

Return type *Param* | *None*

items = None
(List[*Item*]) List of asset product items.

params = None
(List[*Param*]) List of product parameter objects.

product = None
(*Product*) Product object reference.

status = None

Assets may have one of the following statuses:

- new: First purchase requested.
- processing: Until first purchase request is either completed or rejected.
- **active: After the first purchase request is completed.** NOTE: Asset stays active regardless of any other requests except cancel.
- rejected: Asset becomes rejected once the first purchase request is rejected.
- terminated: Asset becomes terminated once the 'cancel' request type is fulfilled.
- suspended: Asset becomes suspended once 'suspend' request type is fulfilled.

tiers = None

(*TierAccounts*) Supply chain accounts.

class `connect.models.BaseModel` (**kwargs)

Base class of all models.

All the arguments provided on creation of the model are injected as attributes on the object.

classmethod `deserialize` (*json_str*)

Deserialize a string containing JSON data into a model.

Parameters `json_str` (*str*) – String containing the JSON data to be deserialized.

Returns An instance of the same class as the receiver of the call, or a list of instances.

Return type Anylist[Any]

Raises **TypeError** – Raised if the data cannot be deserialized.

classmethod `deserialize_json` (*json_data*)

Deserialize JSON data into a model.

Parameters `json_data` (*dict/list*) – JSON list or dictionary to be deserialized.

Returns An instance of the same class as the receiver of the call, or a list of instances.

Return type Anylist[Any]

Raises **TypeError** – Raised if the data cannot be deserialized.

id = None

(str) Globally unique id.

json

Returns The JSON representation of the model.

Return type dictlist

class `connect.models.Company` (**kwargs)

Represents a company within the platform.

name = None

(str) Company name.

class `connect.models.Connection` (**kwargs)

Represents a communication channel which provides the ability to order products within particular hub.

Standalone connection is required for each product and for each provider account.

hub = None

(*Hub*) Hub Reference.

product = None
(*Product*) Product Reference.

provider = None
(*Company*) Provider Account Reference.

type = None
(str) Type of connection.

vendor = None
(*Company*) Vendor Account Reference.

class `connect.models.Constraints` (**kwargs)
Parameter constraints.

choices = None
(List[*ValueChoice*]) Parameter value choices.

hidden = None
(bool) Is the parameter hidden?

required = None
(bool) Is the parameter required?

class `connect.models.Contact` (**kwargs)
Person of contact.

email = None
(str) Email address.

first_name = None
(str|None) First name.

last_name = None
(str|None) Last name.

phone_number = None
(*PhoneNumber*) Phone number.

class `connect.models.ContactInfo` (**kwargs)
Represents the information of a contact.

address_line1 = None
(str) Street address, first line.

address_line2 = None
(str|None) Street address, second line.

city = None
(str) City name.

contact = None
(*Contact*) Person of contact.

country = None
(str) Country code.

postal_code = None
(str) Postal ZIP code.

state = None
(str) State name.

class connect.models.Contract (**kwargs)

Contract object.

activation = None

(*Activation*) Activation information.

agreement = None

(*Agreement*) Reference object to the agreement.

created = None

(datetime.datetime) Contract creation date.

creator = None

(*User*) Reference object to the creator.

enrolled = None

(datetime.datetime|None) Date when contract was enrolled.

marketplace = None

(*Marketplace* | None) Reference object to the agreement marketplace.

name = None

(str) Contract name.

owner = None

(*Company* | None) Reference object to the owner company.

signee = None

(*User* | None) Reference object to the user of the owner company, who signed the contract.

status = None

(str) Contract Status. One of: enrolling, pending, active, terminated, rejected

type = None

(str) Type of the contract (same as agreement type). One of: distribution, program, service.

updated = None

(datetime.datetime) Date of contract status update.

version = None

(int) Version of the contract (same as associated agreement version).

version_created = None

(datetime.datetime) Contract version creation date.

class connect.models.Conversation (**kwargs)

Conversation.

add_message (message, config=None)

Adds a message to the conversation.

Parameters

- **message** (*str*) – Message to add.
- **config** (*Config*) – Configuration, or None to use the environment config (default).

Returns The added message.

Return type *ConversationMessage*

Raises **TypeError** – Raised if the message cannot be deserialized.

created = None

(datetime.datetime) Date of the Conversation creation.

```

creator = None
    (User) Creator of the conversation.

instance_id = None
    (str) The id of object based on which discussion is made, e.g. listing request. It can be any object.

messages = None
    (List[ConversationMessage]) List of ConversationMessage objects.

topic = None
    (str) Conversation topic.

class connect.models.ConversationMessage (**kwargs)
    Message in a Conversation.

conversation = None
    (str) Primary ID of Conversation object.

created = None
    (datetime.datetime) Date of the Message creation.

creator = None
    (User) User that created the message.

text = None
    (str) Actual message.

class connect.models.CustomerUiSettings (**kwargs)
    Customer Ui Settings for a product.

description = None
    (str) Description.

documents = None
    (List[Document]) Documents.

download_links = None
    (List[DownloadLink]) Download links.

getting_started = None
    (str) Getting started.

class connect.models.Document (**kwargs)
    Document for a product.

title = None
    (str) Document title.

url = None
    (str) Document URL.

visible_for = None
    (str) Document visibility. One of: admin, user.

class connect.models.DownloadLink (**kwargs)
    Download link for a product.

title = None
    (str) Link title.

url = None
    (str) Link URL.

```

class `connect.models.EventInfo` (**kwargs)

Represents the date and user that caused an event.

at = None

(datetime.datetime|None) Date when the event occurred.

by = None

(User) User that caused the event.

class `connect.models.Events` (**kwargs)

Represents a set of events that can take place on an object.

created = None

(EventInfo) Creation event.

inquired = None

(EventInfo) Inquire event.

pending = None

(EventInfo) Pending event.

updated = None

(EventInfo) Update event.

validated = None

(EventInfo) Validation event.

class `connect.models.ExtIdHub` (**kwargs)

Associates a *Hub* with an external id.

external_id = None

(str) External id.

hub = None

(Hub) Hub.

class `connect.models.Fulfillment` (**kwargs)

Represents a request for the `connect.resource.FulfillmentAutomation` resource.

activation_key = None

(str) Activation key content for activating the subscription on vendor portal. This markdown formatted message is sent to customer.

asset = None

(Asset) Asset object.

changed_items

Returns Changed items.

Return type List[Item]

contract = None

(Contract) Contract object.

created = None

(datetime.datetime) Date of request creation.

get_conversation (config=None)

Parameters **config** (Config) – Configuration, or None to use the environment config (default).

Returns The conversation for this request, or None if there is none.

Return type Conversation|None

marketplace = None

(*Marketplace*) Marketplace object.

needs_migration (*migration_key='migration_info'*)

Indicates whether the request contains data to be migrated from a legacy product. Migration is performed by an external service. All you have to do for a request that needs migration is to skip processing by raising a *connect.exceptions.SkipRequest* exception.

Parameters migration_key (*str*) – The name of the parameter that contains the migration data (optional; default value is *migration_info*).

Returns Whether the request needs migrating.

Return type bool

new_items

Returns New items.

Return type List[*Item*]

note = None

(*str*) Details of note.

params_form_url = None

(*str*) URL for customer/reseller/provider for modifying param value based on vendor's feedback.

reason = None

(*str*) Fail reason in case of status of request is failed.

removed_items

Returns Removed items.

Return type List[*Item*]

status = None

(*str*) Status of request. One of:

- pending
- inquiring
- failed
- approved

Valid status changes:

- pending -> inquiring
- pending -> failed
- pending -> approved
- inquiring -> failed
- inquiring -> approved
- inquiring -> pending

type = None

(*str*) Asset status. See *Asset* class for details.

updated = None

(*datetime.datetime*) Date of last request modification.

class `connect.models.Hub` (**kwargs)

A Hub.

company = None

(*Company*) Reference to the company the hub belongs to.

description = None

(str|None) Hub description (Markdown text).

events = None

(*Events*) Events occurred on Hub.

instance = None

(*HubInstance*) Hub instance.

name = None

(str) Hub name.

stats = None

(*HubStats*) Hub stats.

class `connect.models.HubInstance` (**kwargs)

An instance of a hub.

type = None

(str) E-Commerce system type.

class `connect.models.HubStats` (**kwargs)

Hub stats.

connections = None

(int) Number of connections active for this Hub.

marketplaces = None

(int) Number of marketplaces for this Hub.

class `connect.models.Item` (**kwargs)

A product item.

global_id = None

(str) Global id.

mpn = None

(str) Item manufacture part number.

old_quantity = None

(int|float|None) Previous value of quantity.

quantity = None

(int|float) Number of items of the type in the asset (-1 if unlimited)

renewal = None

(*Renewal* | None) Parameters of renewal request (empty for all other types).

class `connect.models.Marketplace` (**kwargs)

An object containing Distribution agreements with exact Hubs, enriched with additional information on details about the relation.

A Marketplace is a way to list Products to specified regions (based on Distribution Agreements) and use specific Hubs to provision incoming Fulfillment requests.

active_contracts = None

(int) How many active contracts were signed on the Marketplace.

description = None

(str) Markdown text describing the marketplace.

hubs = None

(List[*ExtIdHub*]) List of account-hub relations associated with the Marketplace object.

icon = None

(str) Image identifying Marketplace object uploaded by user.

name = None

(str) Marketplace title, unique for an account.

owner = None

(*Company*) Provider account - the object owner.

zone = None

(str) Zone where the marketplace is located, there can be following zones: AF, NA, OC, AS, EU, SA (It is continents).

class `connect.models.Param` (**kwargs)

Parameters are used in product and asset definitions.

constraints = None

(*Constraints* | None) Parameter constraints.

description = None

(str) Description of parameter.

name = None

(str) Name of parameter.

scope = None

(str|None) Scope of parameter.

title = None

(str|None) Title for parameter.

type = None

(str) Type of parameter.

value = None

(str) Value of parameter.

value_choice = None

(List[str]|None) Available choices for parameter.

value_error = None

(str|None) Error indicated for parameter.

class `connect.models.PhoneNumber` (**kwargs)

Phone number.

area_code = None

(str|None) Area code.

country_code = None

(str|None) Country code.

extension = None

(str|None) Phone extension.

phone_number = None

(str|None) Phone number.

class `connect.models.Product` (**kwargs)

Represents basic marketing information about salable items, parameters, configurations, latest published version and connections.

It contains basic product information like name, description and logo, along with the latest published version details. So in a single point we can say a single product object always represent the latest published version of that product.

configurations = None

(*ProductConfiguration*) Product configuration.

customer_ui_settings = None

(*CustomerUiSettings*) Customer Ui Settings.

detailed_description = None

(str) Detailed description of product.

icon = None

(str) Product icon URI.

name = None

(str) Product name.

short_description = None

(str) Short description of product.

version = None

(int) Version of product.

class `connect.models.ProductConfiguration` (**kwargs)

Product configurations.

requires_reseller_information = None

(bool) Does the product require reseller information?

suspend_resume_supported = None

(bool) Is suspend and resume supported for the product?

class `connect.models.Renewal` (**kwargs)

Item renewal data.

from_ = None

(datetime.datetime) Date of renewal beginning.

period_delta = None

(int) Size of renewal period.

period_uom = None

(str) Unit of measure for renewal period. One of: year, month, day, hour.

to = None

(datetime.datetime) Date of renewal end.

class `connect.models.ServerErrorResponse` (**kwargs)

Server response when an error occurs.

error_code = None

(str) Error code.

errors = None

(List[str]) List of errors.

params = None

(dict) Error params.


```

class connect.models.Template (**kwargs)
    Tier Template

    representation = None
        (str) Template representation.

class connect.models.TierAccount (**kwargs)
    Tier account.

    contact_info = None
        (ContactInfo) Tier Contact Object.

    external_id = None
        (str|None) Only in case of filtering by this field.

    external_uid = None
        (str|None) Only in case of filtering by this field.

    name = None
        (str) Tier name.

class connect.models.TierAccounts (**kwargs)
    TierAccounts object.

    customer = None
        (TierAccount) Customer Level TierAccount Object.

    tier1 = None
        (TierAccount) Level 1 TierAccount Object.

    tier2 = None
        (TierAccount) Level 2 TierAccount Object.

class connect.models.TierConfig (**kwargs)
    Full representation of Tier object.

    account = None
        (TierAccount) Full tier account representation (same as in Asset).

    connection = None
        (Connection) Reference to Connection Object.

    events = None
        (Events|None) Tier Config events.

classmethod get (tier_id, product_id, config=None)
    Gets the specified tier config data. For example, to get Tier 1 configuration data for one request we can do:

```

```
TierConfig.get(request.asset.tiers.tier1.id, request.asset.product.id)
```

```


```

Parameters

- **tier_id** (*str*) – Id of the requested Tier Config.
- **product_id** (*str*) – Id of the product.
- **config** (*Config*) – Config to use, or None to use environment config (default).

Returns The requested Tier Config, or None if it was not found.

Return type Optional[*TierConfig*]

```

get_param_by_id (id_)
    Get a Tier Config parameter.

```

Parameters `id (str)` – Parameter id.

Returns The requested parameter, or `None` if it was not found.

Return type *Param*

name = None

(str) Tier configuration of account.name.

open_request = None

(*BaseModel* | None) Reference to TCR.

params = None

(List[*Param*]) List of TC parameter data objects as in Asset Object extended with unfilled parameters from product.

product = None

(*Product*) Reference object to product (application).

template = None

(*Template*) Template Object.

tier_level = None

(int) Tier level for product from customer perspective.

class `connect.models.TierConfigRequest (**kwargs)`

activation = None

(*Activation* | None) Activation object. This is created only if TCR has ordering parameters and seen in inquiring state of the TCR.

assignee = None

(*User* | None) TCR environment. One of: test, prod, preview.

configuration = None

(*TierConfig*) Full representation of Tier Configuration Object.

events = None

(*Events* | None) Tier Config request Events.

get_param_by_id (id_)

Get a Tier Config Request parameter.

Parameters `id (str)` – Parameter id.

Returns The requested parameter, or `None` if it was not found.

Return type *Param*

notes = None

(str) TCR pending notes. Notes can be modified only in Pending state.

params = None

(List[*Param*]) List of parameter data objects as in Asset Object. Params can be modified only in Pending state.

reason = None

(str|None) Failing reason. This is filled only if TCR is failed.

status = None

(str) TCR current status. One of: tiers_setup, pending, inquiring, approved, failed.

template = None

(*Template* | None) Template Object. This is filled only if TCR is approved.

type = None
(str) TCR type. One of: setup, update.

class `connect.models.UsageFile` (**kwargs)
Usage File Object.

acceptance_note = None
(str) Note provided by the provider in case of acceptance of the usage file.

accepted_at = None
(str) Usage file acceptance time.

accepted_by = None
(str) User Id, who accepted the usage file as provider.

closed_at = None
(str) Usage file billing time.

closed_by = None
(str) User Id, who billed the usage file as provider.

contract = None
(*Contract*) Reference on Contract Object.

created_at = None
(str) Date of the creation of the UsageFile.

created_by = None
(str) User ID who have created this UsageFile.

description = None
(str) Vendor can provide a description value in this field to describe the file content.

error_details = None
(str) In case of invalid file, this field will contain errors related to the file.

marketplace = None
(*Marketplace*) Reference on Marketplace Object.

name = None
(str) Name of the Usage file object.

note = None
(str) Vendor can put a note which can be refer later for some extra information.

processed_file_uri = None
(str) Google Storage shared location of the generated file after processing uploaded file. Only available in GET API and not included in list API (sharing timeout 30 sec).

product = None
(*Product*) Reference on Product Object.

provider = None
(*Company*) Reference object to the provider company.

records = None
(*UsageRecords*) UsageRecords Object.

rejected_at = None
(str) Usage file rejection time.

rejected_by = None
(str) User Id, who rejected the usage file as provider.

rejection_note = None

(str) Note provider by the provider in case of rejection of the usage file.

status = None

(str) One of: draft, uploading, uploaded, processing, invalid, ready, rejected, pending, accepted, closed.

submitted_at = None

(str) User Id, who submitted the usage record to Provider.

submitted_by = None

(str) User Id, who submitted the usage record to Provider.

upload_file_uri = None

(str) Google Storage shared location of the upload file. Only available in GET API and not included in list API (sharing timeout 600 sec).

uploaded_at = None

(str) Usage file upload time.

uploaded_by = None

(str) User Id who uploaded the file.

vendor = None

(*Company*) Reference object to the vendor company.

class connect.models.UsageListing (**kwargs)

Usage Listing Object.

contract = None

(*Contract*) Contract Object.

created = None

(str) Creation time.

product = None

(*Product*) Product Object.

provider = None

(*Company*) Provider Object.

status = None

(str) Status.

vendor = None

(*Company*) Vendor Object.

class connect.models.UsageRecord (**kwargs)

Usage Record Object.

asset_search_criteria = None

(str) Asset search criteria.

asset_search_value = None

(str) Asset search value.

end_time_utc = None

(str) End Time in UTC.

item_search_criteria = None

(str) Item search criteria.

item_search_value = None

(str) Item search value.

quantity = None
(int) Quantity.

record_id = None
(str) Record id.

start_time_utc = None
(str) Start Time in UTC.

class `connect.models.UsageRecords` (**kwargs)
Usage Records Object.

invalid = None
(int) Invalid.

valid = None
(int) Valid.

class `connect.models.User` (**kwargs)
Represents a user within the platform.

name = None
(str) User name.

class `connect.models.ValueChoice` (**kwargs)
A value choice for a parameter.

label = None
(str) Label.

value = None
(str) Value.

2.2.4 resources

class `connect.resources.FulfillmentAutomation` (*config=None*)

This is the automation engine for the Fulfillment API. If you want to process fulfillment requests, subclass this and implement the `process_request` method, which receives a `connect.models.Fulfillment` request as argument and must return an `ActivationTemplateResponse` or `ActivationTileResponse` object in case the request has to be approved.

In other case, you must raise one of these exceptions:

- `connect.models.InquireRequest`: Inquire for more information.
- `connect.models.FailRequest`: Causes the request to fail.
- `connect.models.SkipRequest`: Skips processing the request.

Create an instance of your subclass and call its `process` method to begin processing.

For an example on how to use this class, see [Processing Fulfillment Requests](#).

filters (*status='pending', **kwargs*)

Parameters

- **status** (*str*) – Status of the requests. Default: 'pending'.
- **kwargs** (*dict[str, Any]*) – Additional filters to add to the default ones.

Returns The set of filters for this resource.

Return type `dict[str, Any]`

get_tier_config (*tier_id, product_id*)

Gets the specified tier config data. For example, to get Tier 1 configuration data for one request, within the FulfillmentAutomation instance, we can do:

```
self.get_tier_config(request.asset.tiers.tier1.id, request.asset.product.id)
```

Parameters

- **tier_id** (*str*) – Id of the requested Tier Config.
- **product_id** (*str*) – Id of the product.

Returns The requested Tier Config, or None if it was not found.

Return type Optional[TierConfig]

Deprecated since version 16.0: Use TierConfig.get instead.

model_class

alias of connect.models.fulfillment.Fulfillment

update_parameters (*pk, params*)

Sends a list of Param objects to Connect for updating.

Parameters

- **pk** (*str*) – Id of the request.
- **params** (*list [Param]*) – List of parameters to update.

Returns The server response.

Return type str

class connect.resources.TemplateResource (*config=None*)

Template Resource.

get (*pk*)

Get an activation template.

Parameters **pk** (*str*) – Primary key of the template to obtain.

Returns ActivationTemplateResponse object with template contents.

Return type ActivationTemplateResponse

render (*pk, request_id*)

Get an activation tile.

Parameters

- **pk** (*str*) – Primary key of the template to obtain.
- **request_id** (*str*) – Id of the associated request.

Returns ActivationTileResponse object with tile contents.

Return type ActivationTileResponse

class connect.resources.TierConfigAutomation (*config=None*)

This is the automation engine for the Tier Config Request API. If you want to process Tier Config requests, subclass this and implement the process_request method, which receives a connect.models.TierConfigRequest request as argument and must return an ActivationTemplateResponse or ActivationTileResponse object in case the request has to be approved.

In other case, you must raise one of these exceptions:

- `connect.models.InquireRequest`: Inquire for more information.
- `connect.models.FailRequest`: Causes the request to fail.
- `connect.models.SkipRequest`: Skips processing the request.

Create an instance of your subclass and call its `process` method to begin processing.

For an example on how to use this class, see [Processing Tier Config Requests](#).

model_class

alias of `connect.models.tier_config.TierConfigRequest`

update_parameters (*pk, params*)

Sends a list of Param objects to Connect for updating.

Parameters

- **pk** (*str*) – Id of the request.
- **params** (*list [Param]*) – List of parameters to update.

Returns The server response.

Return type `str`

class `connect.resources.UsageAutomation` (*config=None*)

Automates reporting of Usage Files.

For an example on how to use this class, see [Reporting Usage Files](#).

filters (*status='listed', **kwargs*)

Parameters

- **status** (*str*) – Status of the requests. Default: 'listed'.
- **kwargs** (*dict [str, Any]*) – Additional filters to add to the default ones.

Returns The set of filters for this resource.

Return type `dict[str,Any]`

get_usage_template (*product*)

Returns the template file contents for a specified product.

Parameters **product** (`Product`) – Specific product.

Returns The template file contents.

Return type `bytes`

Raises `FileRetrievalError` – Raised if the file contents could not be retrieved.

model_class

alias of `connect.models.usage.UsageFile`

submit_usage (*usage_file, usage_records*)

Submit a usage file.

Parameters

- **usage_file** (`UsageFile`) – Usage file.
- **usage_records** (*list [UsageRecord]*) – Records.

Returns Usage file.

Return type `UsageFile`

Raises *FileCreationError* – Raised if creation or uploading of the file fails.

class `connect.resources.UsageFileAutomation` (*config=None*)
Automates workflow of Usage Files.

For an example on how to use this class, see *Workflow of Usage Files*.

model_class
alias of `connect.models.usage.UsageFile`

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

C

`connect.config`, 8
`connect.exceptions`, 8
`connect.models`, 9
`connect.resources`, 25

A

acceptance_note (*connect.models.UsageFile attribute*), 23

accepted_at (*connect.models.UsageFile attribute*), 23

accepted_by (*connect.models.UsageFile attribute*), 23

AcceptUsageFile, 8

account (*connect.models.TierConfig attribute*), 21

Activation (*class in connect.models*), 9

activation (*connect.models.Contract attribute*), 14

activation (*connect.models.TierConfigRequest attribute*), 22

activation_key (*connect.models.Fulfillment attribute*), 16

active (*connect.models.Agreement attribute*), 10

active_contracts (*connect.models.Marketplace attribute*), 18

add_message() (*connect.models.Conversation method*), 14

address_line1 (*connect.models.ContactInfo attribute*), 13

address_line2 (*connect.models.ContactInfo attribute*), 13

Agreement (*class in connect.models*), 10

agreement (*connect.models.Contract attribute*), 14

agreements (*connect.models.Agreement attribute*), 10

AgreementStats (*class in connect.models*), 10

api_key (*connect.config.Config attribute*), 8

api_url (*connect.config.Config attribute*), 8

area_code (*connect.models.PhoneNumber attribute*), 19

Asset (*class in connect.models*), 11

asset (*connect.models.Fulfillment attribute*), 16

asset_search_criteria (*connect.models.UsageRecord attribute*), 24

asset_search_value (*connect.models.UsageRecord attribute*), 24

assignee (*connect.models.TierConfigRequest at-*

tribute), 22

at (*connect.models.EventInfo attribute*), 16

author (*connect.models.Agreement attribute*), 10

B

BaseModel (*class in connect.models*), 12

by (*connect.models.EventInfo attribute*), 16

C

changed_items (*connect.models.Fulfillment attribute*), 16

choices (*connect.models.Constraints attribute*), 13

city (*connect.models.ContactInfo attribute*), 13

closed_at (*connect.models.UsageFile attribute*), 23

closed_by (*connect.models.UsageFile attribute*), 23

CloseUsageFile, 8

code (*connect.exceptions.Message attribute*), 9

Company (*class in connect.models*), 12

company (*connect.models.Hub attribute*), 18

Config (*class in connect.config*), 8

configuration (*connect.models.TierConfigRequest attribute*), 22

configurations (*connect.models.Product attribute*), 20

connect.config (*module*), 8

connect.exceptions (*module*), 8

connect.models (*module*), 9

connect.resources (*module*), 25

Connection (*class in connect.models*), 12

connection (*connect.models.Asset attribute*), 11

connection (*connect.models.TierConfig attribute*), 21

connections (*connect.models.HubStats attribute*), 18

Constraints (*class in connect.models*), 13

constraints (*connect.models.Param attribute*), 19

Contact (*class in connect.models*), 13

contact (*connect.models.ContactInfo attribute*), 13

contact_info (*connect.models.TierAccount attribute*), 21

ContactInfo (*class in connect.models*), 13

Contract (class in connect.models), 13
 contract (connect.models.Fulfillment attribute), 16
 contract (connect.models.UsageFile attribute), 23
 contract (connect.models.UsageListing attribute), 24
 contracts (connect.models.AgreementStats attribute), 10
 Conversation (class in connect.models), 14
 conversation (connect.models.ConversationMessage attribute), 15
 ConversationMessage (class in connect.models), 15
 country (connect.models.ContactInfo attribute), 13
 country_code (connect.models.PhoneNumber attribute), 19
 created (connect.models.Agreement attribute), 10
 created (connect.models.Contract attribute), 14
 created (connect.models.Conversation attribute), 14
 created (connect.models.ConversationMessage attribute), 15
 created (connect.models.Events attribute), 16
 created (connect.models.Fulfillment attribute), 16
 created (connect.models.UsageListing attribute), 24
 created_at (connect.models.UsageFile attribute), 23
 created_by (connect.models.UsageFile attribute), 23
 creator (connect.models.Contract attribute), 14
 creator (connect.models.Conversation attribute), 14
 creator (connect.models.ConversationMessage attribute), 15
 customer (connect.models.TierAccounts attribute), 21
 customer_ui_settings (connect.models.Product attribute), 20
 CustomerUiSettings (class in connect.models), 15

D

date (connect.models.Activation attribute), 9
 DeleteUsageFile, 8
 description (connect.models.Agreement attribute), 10
 description (connect.models.CustomerUiSettings attribute), 15
 description (connect.models.Hub attribute), 18
 description (connect.models.Marketplace attribute), 18
 description (connect.models.Param attribute), 19
 description (connect.models.UsageFile attribute), 23
 deserialize() (connect.models.BaseModel class method), 12
 deserialize_json() (connect.models.BaseModel class method), 12
 detailed_description (connect.models.Product attribute), 20
 Document (class in connect.models), 15

documents (connect.models.CustomerUiSettings attribute), 15
 download_links (connect.models.CustomerUiSettings attribute), 15
 DownloadLink (class in connect.models), 15

E

email (connect.models.Contact attribute), 13
 end_time_utc (connect.models.UsageRecord attribute), 24
 enrolled (connect.models.Contract attribute), 14
 error_code (connect.models.ServerErrorResponse attribute), 20
 error_details (connect.models.UsageFile attribute), 23
 errors (connect.models.ServerErrorResponse attribute), 20
 EventInfo (class in connect.models), 15
 Events (class in connect.models), 16
 events (connect.models.Hub attribute), 18
 events (connect.models.TierConfig attribute), 21
 events (connect.models.TierConfigRequest attribute), 22
 extension (connect.models.PhoneNumber attribute), 19
 external_id (connect.models.Asset attribute), 11
 external_id (connect.models.ExtIdHub attribute), 16
 external_id (connect.models.TierAccount attribute), 21
 external_uid (connect.models.Asset attribute), 11
 external_uid (connect.models.TierAccount attribute), 21
 ExtIdHub (class in connect.models), 16

F

FailRequest, 8
 FileCreationError, 8
 FileRetrievalError, 8
 filters() (connect.resources.FulfillmentAutomation method), 25
 filters() (connect.resources.UsageAutomation method), 27
 first_name (connect.models.Contact attribute), 13
 from_ (connect.models.Renewal attribute), 20
 Fulfillment (class in connect.models), 16
 FulfillmentAutomation (class in connect.resources), 25

G

get () (connect.models.TierConfig class method), 21
 get () (connect.resources.TemplateResource method), 26

get_conversation() (*connect.models.Fulfillment method*), 16
 get_instance() (*connect.config.Config class method*), 8
 get_item_by_mpn() (*connect.models.Asset method*), 11
 get_param_by_id() (*connect.models.Asset method*), 11
 get_param_by_id() (*connect.models.TierConfig method*), 21
 get_param_by_id() (*connect.models.TierConfigRequest method*), 22
 get_tier_config() (*connect.resources.FulfillmentAutomation method*), 25
 get_usage_template() (*connect.resources.UsageAutomation method*), 27
 getting_started (*connect.models.CustomerUiSettings attribute*), 15
 global_id (*connect.models.Item attribute*), 18

H

hidden (*connect.models.Constraints attribute*), 13
 Hub (*class in connect.models*), 17
 hub (*connect.models.Connection attribute*), 12
 hub (*connect.models.ExtIdHub attribute*), 16
 HubInstance (*class in connect.models*), 18
 hubs (*connect.models.Marketplace attribute*), 19
 HubStats (*class in connect.models*), 18

I

icon (*connect.models.Marketplace attribute*), 19
 icon (*connect.models.Product attribute*), 20
 id (*connect.models.BaseModel attribute*), 12
 inquired (*connect.models.Events attribute*), 16
 InquireRequest, 9
 instance (*connect.models.Hub attribute*), 18
 instance_id (*connect.models.Conversation attribute*), 15
 invalid (*connect.models.UsageRecords attribute*), 25
 Item (*class in connect.models*), 18
 item_search_criteria (*connect.models.UsageRecord attribute*), 24
 item_search_value (*connect.models.UsageRecord attribute*), 24
 items (*connect.models.Asset attribute*), 11

J

json (*connect.models.BaseModel attribute*), 12

L

label (*connect.models.ValueChoice attribute*), 25
 last_name (*connect.models.Contact attribute*), 13
 link (*connect.models.Activation attribute*), 10
 link (*connect.models.Agreement attribute*), 10

M

Marketplace (*class in connect.models*), 18
 marketplace (*connect.models.Agreement attribute*), 10
 marketplace (*connect.models.Contract attribute*), 14
 marketplace (*connect.models.Fulfillment attribute*), 17
 marketplace (*connect.models.UsageFile attribute*), 23
 marketplaces (*connect.models.HubStats attribute*), 18
 Message, 9
 message (*connect.exceptions.Message attribute*), 9
 message (*connect.models.Activation attribute*), 10
 messages (*connect.models.Conversation attribute*), 15
 model_class (*connect.resources.FulfillmentAutomation attribute*), 26
 model_class (*connect.resources.TierConfigAutomation attribute*), 27
 model_class (*connect.resources.UsageAutomation attribute*), 27
 model_class (*connect.resources.UsageFileAutomation attribute*), 28
 mpn (*connect.models.Item attribute*), 18

N

name (*connect.models.Company attribute*), 12
 name (*connect.models.Contract attribute*), 14
 name (*connect.models.Hub attribute*), 18
 name (*connect.models.Marketplace attribute*), 19
 name (*connect.models.Param attribute*), 19
 name (*connect.models.Product attribute*), 20
 name (*connect.models.TierAccount attribute*), 21
 name (*connect.models.TierConfig attribute*), 22
 name (*connect.models.UsageFile attribute*), 23
 name (*connect.models.User attribute*), 25
 needs_migration() (*connect.models.Fulfillment method*), 17
 new_items (*connect.models.Fulfillment attribute*), 17
 note (*connect.models.Fulfillment attribute*), 17
 note (*connect.models.UsageFile attribute*), 23
 notes (*connect.models.TierConfigRequest attribute*), 22

O

obj (*connect.exceptions.Message attribute*), 9
 old_quantity (*connect.models.Item attribute*), 18
 open_request (*connect.models.TierConfig attribute*), 22

owner (*connect.models.Agreement* attribute), 10
 owner (*connect.models.Contract* attribute), 14
 owner (*connect.models.Marketplace* attribute), 19

P

Param (*class in connect.models*), 19
 params (*connect.exceptions.InquireRequest* attribute), 9
 params (*connect.models.Asset* attribute), 11
 params (*connect.models.ServerErrorResponse* attribute), 20
 params (*connect.models.TierConfig* attribute), 22
 params (*connect.models.TierConfigRequest* attribute), 22
 params_form_url (*connect.models.Fulfillment* attribute), 17
 parent (*connect.models.Agreement* attribute), 10
 pending (*connect.models.Events* attribute), 16
 period_delta (*connect.models.Renewal* attribute), 20
 period_uom (*connect.models.Renewal* attribute), 20
 phone_number (*connect.models.Contact* attribute), 13
 phone_number (*connect.models.PhoneNumber* attribute), 19
 PhoneNumber (*class in connect.models*), 19
 postal_code (*connect.models.ContactInfo* attribute), 13
 processed_file_uri (*connect.models.UsageFile* attribute), 23
 Product (*class in connect.models*), 19
 product (*connect.models.Asset* attribute), 11
 product (*connect.models.Connection* attribute), 12
 product (*connect.models.TierConfig* attribute), 22
 product (*connect.models.UsageFile* attribute), 23
 product (*connect.models.UsageListing* attribute), 24
 ProductConfiguration (*class in connect.models*), 20
 products (*connect.config.Config* attribute), 8
 provider (*connect.models.Connection* attribute), 13
 provider (*connect.models.UsageFile* attribute), 23
 provider (*connect.models.UsageListing* attribute), 24

Q

quantity (*connect.models.Item* attribute), 18
 quantity (*connect.models.UsageRecord* attribute), 24

R

reason (*connect.models.Fulfillment* attribute), 17
 reason (*connect.models.TierConfigRequest* attribute), 22
 record_id (*connect.models.UsageRecord* attribute), 25
 records (*connect.models.UsageFile* attribute), 23
 rejected_at (*connect.models.UsageFile* attribute), 23

rejected_by (*connect.models.UsageFile* attribute), 23
 rejection_note (*connect.models.UsageFile* attribute), 23
 RejectUsageFile, 9
 removed_items (*connect.models.Fulfillment* attribute), 17
 render () (*connect.resources.TemplateResource* method), 26
 Renewal (*class in connect.models*), 20
 renewal (*connect.models.Item* attribute), 18
 representation (*connect.models.Template* attribute), 21
 required (*connect.models.Constraints* attribute), 13
 requires_reseller_information (*connect.models.ProductConfiguration* attribute), 20

S

scope (*connect.models.Param* attribute), 19
 ServerError, 9
 ServerErrorResponse (*class in connect.models*), 20
 short_description (*connect.models.Product* attribute), 20
 signee (*connect.models.Contract* attribute), 14
 SkipRequest, 9
 start_time_utc (*connect.models.UsageRecord* attribute), 25
 state (*connect.models.ContactInfo* attribute), 13
 stats (*connect.models.Agreement* attribute), 10
 stats (*connect.models.Hub* attribute), 18
 status (*connect.models.Asset* attribute), 11
 status (*connect.models.Contract* attribute), 14
 status (*connect.models.Fulfillment* attribute), 17
 status (*connect.models.TierConfigRequest* attribute), 22
 status (*connect.models.UsageFile* attribute), 24
 status (*connect.models.UsageListing* attribute), 24
 submit_usage () (*connect.resources.UsageAutomation* method), 27
 submitted_at (*connect.models.UsageFile* attribute), 24
 submitted_by (*connect.models.UsageFile* attribute), 24
 SubmitUsageFile, 9
 suspend_resume_supported (*connect.models.ProductConfiguration* attribute), 20

T

Template (*class in connect.models*), 20
 template (*connect.models.TierConfig* attribute), 22

template (*connect.models.TierConfigRequest attribute*), 22

TemplateResource (*class in connect.resources*), 26

text (*connect.models.ConversationMessage attribute*), 15

tier1 (*connect.models.TierAccounts attribute*), 21

tier2 (*connect.models.TierAccounts attribute*), 21

tier_level (*connect.models.TierConfig attribute*), 22

TierAccount (*class in connect.models*), 21

TierAccounts (*class in connect.models*), 21

TierConfig (*class in connect.models*), 21

TierConfigAutomation (*class in connect.resources*), 26

TierConfigRequest (*class in connect.models*), 22

tiers (*connect.models.Asset attribute*), 12

title (*connect.models.Agreement attribute*), 10

title (*connect.models.Document attribute*), 15

title (*connect.models.DownloadLink attribute*), 15

title (*connect.models.Param attribute*), 19

to (*connect.models.Renewal attribute*), 20

topic (*connect.models.Conversation attribute*), 15

type (*connect.models.Agreement attribute*), 10

type (*connect.models.Connection attribute*), 13

type (*connect.models.Contract attribute*), 14

type (*connect.models.Fulfillment attribute*), 17

type (*connect.models.HubInstance attribute*), 18

type (*connect.models.Param attribute*), 19

type (*connect.models.TierConfigRequest attribute*), 22

U

update_parameters() (*connect.resources.FulfillmentAutomation method*), 26

update_parameters() (*connect.resources.TierConfigAutomation method*), 27

updated (*connect.models.Agreement attribute*), 10

updated (*connect.models.Contract attribute*), 14

updated (*connect.models.Events attribute*), 16

updated (*connect.models.Fulfillment attribute*), 17

upload_file_uri (*connect.models.UsageFile attribute*), 24

uploaded_at (*connect.models.UsageFile attribute*), 24

uploaded_by (*connect.models.UsageFile attribute*), 24

url (*connect.models.Document attribute*), 15

url (*connect.models.DownloadLink attribute*), 15

UsageAutomation (*class in connect.resources*), 27

UsageFile (*class in connect.models*), 23

UsageFileAction, 9

UsageFileAutomation (*class in connect.resources*), 28

UsageListing (*class in connect.models*), 24

UsageRecord (*class in connect.models*), 24

UsageRecords (*class in connect.models*), 25

User (*class in connect.models*), 25

V

valid (*connect.models.UsageRecords attribute*), 25

validated (*connect.models.Events attribute*), 16

value (*connect.models.Param attribute*), 19

value (*connect.models.ValueChoice attribute*), 25

value_choice (*connect.models.Param attribute*), 19

value_error (*connect.models.Param attribute*), 19

ValueChoice (*class in connect.models*), 25

vendor (*connect.models.Connection attribute*), 13

vendor (*connect.models.UsageFile attribute*), 24

vendor (*connect.models.UsageListing attribute*), 24

version (*connect.models.Agreement attribute*), 10

version (*connect.models.Contract attribute*), 14

version (*connect.models.Product attribute*), 20

version_contracts (*connect.models.Agreement attribute*), 10

version_created (*connect.models.Agreement attribute*), 10

version_created (*connect.models.Contract attribute*), 14

versions (*connect.models.AgreementStats attribute*), 11

visible_for (*connect.models.Document attribute*), 15

Z

zone (*connect.models.Marketplace attribute*), 19