
Connect SDK Documentation

Ingram Micro

Sep 01, 2020

Contents

1	Introduction	1
1.1	Installation	2
1.2	Requirements	2
2	Contents	3
2.1	Examples	3
2.2	API Reference	8
3	Indices and tables	45
	Python Module Index	47
	Index	49

Connect Python SDK allows an easy and fast integration with Connect fulfillment API. Thanks to it you can automate the fulfillment of orders generated by your products.

In order to use this library, please ensure that you have read first the documentation available on Connect knowledge base article located [here](#), this one will provide you a great information on the REST API that this library implements.

This library may be consumed in your project in order to automate the fulfillment of requests, this class once imported into your project will allow you to:

- Communicate with Connect using your API credentials.
- **List all requests, and even filter them:**
 - For a specific product.
 - For a specific status.
 - For a specific asset.
 - Etc.
- Process each request and obtain full details of the request.
- **Modify the activation parameters of each request in order to:**
 - Inquiry for changes
 - Store information into the fulfillment request
- Change the status of the requests from its initial pending state to either inquiring, failed or approved.
- Generate and upload usage files to report usage for active contracts and listings.
- Process usage file status changes.
- Work with Notes for requests.
- Generate logs.
- Collect debug logs in case of failure.

Your code may use any scheduler to execute, from a simple cron to a cloud scheduler like the ones available in Azure, Google, Amazon or other cloud platforms.

1.1 Installation

In order to use the SDK with your product, you must install the `connect-sdk` package from [PyPI \(Python Package Index\)](#). You can do so using `pip`:

```
$ pip install connect-sdk
```

1.2 Requirements

- Python 2.7+ or Python 3.4+
- Requests
- Marshmallow

2.1 Examples

2.1.1 Processing Fulfillment Requests

```
# -*- coding: utf-8 -*-  
  
# This file is part of the Ingram Micro Cloud Blue Connect SDK.  
# Copyright (c) 2019-2020 Ingram Micro. All Rights Reserved.  
  
from typing import Union  
import warnings  
  
from connect.config import Config  
from connect.exceptions import FailRequest, InquireRequest, SkipRequest  
from connect.logger import logger  
from connect.models import ActivationTemplateResponse, ActivationTileResponse,  
↳ Fulfillment  
from connect.resources import FulfillmentAutomation  
  
# Enable processing of deprecation warnings  
warnings.simplefilter('default')  
  
# Set logger level / default level ERROR  
logger.setLevel('DEBUG')  
  
# If we remove this line, it is done implicitly  
Config(file='config.json')  
  
class FulfillmentExample(FulfillmentAutomation):  
    def process_request(self, request):  
        # type: (Fulfillment) -> Union[ActivationTemplateResponse,  
↳ ActivationTileResponse]
```

(continues on next page)

```

    if request.needs_migration():
        # Skip request if it needs migration (migration is performed by an
↪external service)
        logger.info('Skipping request {} because it needs migration.'.
↪format(request.id))
        raise SkipRequest()
    else:
        logger.info('Processing request {} for contract {}, product {},
↪marketplace {}'.format(request.id,
                            request.contract.id,
                            request.asset.product.name,
                            request.marketplace.name))

        # Custom logic
        if request.type == 'purchase':
            for item in request.asset.items:
                if item.quantity > 100000:
                    raise FailRequest('Is not possible to purchase product in
↪such quantities')

            for param in request.asset.params:
                if param.name == 'email' and not param.value:
                    param.value_error = 'Email address has not been provided, ' \
                                        'please provide one'
                    raise InquireRequest(params=[param])

            # Find a param by its id
            param = request.asset.get_param_by_id('purchase_id')
            if param:
                param.value = '...' # We can assign the id given by the external
↪service here
                self.update_parameters(request.id, [param]) # Update param on
↪the platform
            else:
                raise FailRequest('The asset is expected to have a "purchase_id"
↪param.')

            # Approve by Template
            return ActivationTemplateResponse('TL-497-535-242')
            # Or
            # return TemplateResource().get(pk='TEMPLATE_ID')

            # Approve by ActivationTile
            # return ActivationTileResponse('\n # Welcome to Fallball!\n\nYes,
↪you decided '
            #                                     'to have an account in our amazing
↪service!')
            # Or
            # return TemplateResource().render(pk='TEMPLATE_ID', request_
↪id=request.id)

        elif request.type == 'change':
            # Fail
            raise FailRequest()
        else:

```

(continues on next page)

(continued from previous page)

```

        # Skip request
        raise SkipRequest()

if __name__ == '__main__':
    fulfillment_example = FulfillmentExample()
    fulfillment_example.process()

```

2.1.2 Processing Tier Config Requests

```

# -*- coding: utf-8 -*-

# This file is part of the Ingram Micro Cloud Blue Connect SDK.
# Copyright (c) 2019-2020 Ingram Micro. All Rights Reserved.

# NOTE: This example development is in progress. This is just a skeleton.

from typing import Union
import warnings

from connect.config import Config
from connect.logger import logger
from connect.models import ActivationTemplateResponse, ActivationTileResponse, \
↳TierConfigRequest
from connect.resources import TierConfigAutomation

# Enable processing of deprecation warnings
warnings.simplefilter('default')

# Set logger level / default level ERROR
logger.setLevel('DEBUG')

# If we remove this line, it is done implicitly
Config(file='./examples/config.json')

class TierConfigExample(TierConfigAutomation):

    def process_request(self, request):
        # type: (TierConfigRequest) -> Union[ActivationTemplateResponse, \
↳ActivationTileResponse]
        pass

if __name__ == '__main__':
    tier_config_example = TierConfigExample()
    tier_config_example.process()

```

2.1.3 Reporting Usage Files

```

# -*- coding: utf-8 -*-

```

(continues on next page)

```
# This file is part of the Ingram Micro Cloud Blue Connect SDK.
# Copyright (c) 2019-2020 Ingram Micro. All Rights Reserved.

from datetime import datetime, timedelta
import warnings

from connect.config import Config
from connect.logger import logger
from connect.models import Contract, UsageRecord, UsageFile, UsageListing, Product
from connect.resources import UsageAutomation

# Enable processing of deprecation warnings
warnings.simplefilter('default')

# Set logger level / default level ERROR
logger.setLevel('DEBUG')

# If we remove this line, it is done implicitly
Config(file='config.json')

class UsageExample(UsageAutomation):
    def process_request(self, request):
        # type: (UsageListing) -> None

        # Detect specific provider contract
        if request.contract.id == 'CRD-00000-00000-00000':
            # Can also be seen from request.provider.id and parametrized further
            # via marketplace available at request.marketplace.id
            usage_file = UsageFile(
                name='sdk test',
                product=Product(id=request.product.id),
                contract=Contract(id=request.contract.id)
            )

            today = datetime.utcnow().replace(hour=0, minute=0, second=0,
↪microsecond=0)
            yesterday = today - timedelta(days=1)

            usages = [
                UsageRecord(
                    usage_record_id='unique record value',

                    item_search_criteria='item.mpn',
                    # Possible values are item.mpn or item.local_id.

                    item_search_value='SKUA',
                    # Value defined as MPN on vendor portal.

                    quantity=1,
                    # Quantity to be reported.

                    start_time_utc=yesterday.strftime('%Y-%m-%d %H:%M:%S'),
                    # From when to report.

                    end_time_utc=today.strftime('%Y-%m-%d %H:%M:%S'),
                    # Till when to report.
```

(continues on next page)

(continued from previous page)

```

        asset_search_criteria='parameter.param_b',
        # How to find the asset on Connect. Typical use case is to use a
↪parameter
        # provided by vendor, in this case called param_b. Additionally,
↪asset.id
        # can be used in case you want to use Connect identifiers.

        asset_search_value='tenant2'
    )
]

self.submit_usage(usage_file, usages)
else:
    # Something different could be done here
    pass

if __name__ == '__main__':
    usage_example = UsageExample()
    usage_example.process()

```

2.1.4 Workflow of Usage Files

```

# -*- coding: utf-8 -*-

# This file is part of the Ingram Micro Cloud Blue Connect SDK.
# Copyright (c) 2019-2020 Ingram Micro. All Rights Reserved.

import warnings

from connect.config import Config
from connect.logger import logger
from connect.exceptions import AcceptUsageFile, DeleteUsageFile, SkipRequest,
↪SubmitUsageFile
from connect.models import UsageFile
from connect.resources import UsageFileAutomation

# Enable processing of deprecation warnings
warnings.simplefilter('default')

# Set logger level / default level ERROR
logger.setLevel('DEBUG')

# If we remove this line, it is done implicitly
Config(file='config.json')

class UsageFileExample(UsageFileAutomation):
    def process_request(self, request):
        # type: (UsageFile) -> None
        if request.status == 'invalid':
            # Vendor and provider may handle invalid cases differently,
            # probably notifying their staff
            raise DeleteUsageFile('Not needed anymore')

```

(continues on next page)

```
elif request.status == 'ready':
    # Vendor may submit file to provider
    raise SubmitUsageFile()
elif request.status == 'pending':
    # Provider use case, needs to be reviewed and accepted
    raise AcceptUsageFile('File looks good')
else:
    raise SkipRequest('Non controlled status')

if __name__ == '__main__':
    usage_file_example = UsageFileExample()
    usage_file_example.process()
```

2.2 API Reference

2.2.1 config

class `connect.config.Config` (*api_url=None, api_key=None, products=None, file=None*)
Initialization config for public api.

Parameters

- **api_url** (*str*) – Public api url.
- **api_key** (*str*) – Service user ApiKey.
- **products** (*str/list[str]*) – Optional product ids.
- **file** (*str*) – Config file name.

Raises

- **ValueError** – Raised if either `file` or one of `api_url` or `api_key` are missing.
- **TypeError** – Raised if `products` is not a string or list of strings, or if config file does not contain JSON data.
- **IOError** – Raised if the specified `file` could not be opened.

`api_key`

Returns ApiKey.

Return type str

`api_url`

Returns Api URL.

Return type str

classmethod `get_instance()`

Returns Global instance.

Return type *Config*

products

Returns Valid product ids.

Return type list[str]

2.2.2 exceptions

exception `connect.exceptions.AcceptUsageFile` (*acceptance_note*)

exception `connect.exceptions.CloseUsageFile` (*message=None*)

exception `connect.exceptions.DeleteUsageFile` (*message=None*)

exception `connect.exceptions.FailRequest` (*message=""*)

Causes the request being processed to fail.

Parameters `message` (*str*) – Exception message.

exception `connect.exceptions.FileCreationError` (*message*)

exception `connect.exceptions.FileRetrievalError` (*message*)

exception `connect.exceptions.InquireRequest` (*message=""*, *params=None*)

Causes the request being processed to inquire for some information.

Parameters

- `message` (*str*) – Exception message.
- `params` (*List[Param]*) – Parameters to inquire.

params = None

(*List[Param]*) Parameters to inquire.

exception `connect.exceptions.Message` (*message=""*, *code=""*, *obj=None*)

Base class for all Connect exceptions.

Parameters

- `message` (*str*) – Exception message.
- `code` (*str*) – Exception code.
- `obj` (*object*) – Additional information.

code = None

(*str*) Exception code.

message

Returns The exception message.

Return type str

Deprecated since version 16.0: Use `str(exception)` instead.

obj = None

(*str*) Additional information.

exception `connect.exceptions.RejectUsageFile` (*rejection_note*)

exception `connect.exceptions.ServerError` (*error*)

Indicates that the server returned an error.

Parameters `error` (*ServerErrorResponse*) – Response returned by the server.

exception `connect.exceptions.SkipRequest` (*message=""*)

Causes the request being processed to be skipped.

Parameters `message` (*str*) – Exception message.

exception `connect.exceptions.SubmitUsageFile`

exception `connect.exceptions.UsageFileAction` (*message*, *code*, *data=None*)
Base exception for Usage API actions.

Parameters

- **message** (*str*) – Exception message.
- **code** (*str*) – Exception code.
- **data** (*Optional[Dict[str, Any]]*) – Additional information.

2.2.3 models

class `connect.models.Activation` (***kwargs*)
Activation object.

date = None
(`datetime.datetime|None`) Activation date.

link = None
(`str|None`) Activation link.

message = None
(`str`) Activation message.

class `connect.models.ActivationTemplateResponse` (*template_id*)
An instance of this class might be returned by the overridden `process_request` method of your `connect.resources.FulfillmentAutomation` or `connect.resources.TierConfigAutomation` subclass to approve the request being processed, showing a tile with the specified template id.

Parameters **template_id** (*str*) – Id of the template of the tile to be shown in the Vendor Portal.
The template must have been defined in the Vendor Portal.

Return type `None`

class `connect.models.ActivationTileResponse` (*markdown=""*)
An instance of this class might be returned by the overridden `process_request` method of your `connect.resources.FulfillmentAutomation` or `connect.resources.TierConfigAutomation` subclass to approve the request being processed, showing a tile with the specified contents.

Parameters **markdown** (*str*) – Contents of the tile to be shown in the Vendor Portal, in Markdown format.

Return type `None`

class `connect.models.Agreement` (***kwargs*)
An Agreement object.

active = None
(`bool`) State of the version.

agreements = None
(`List[Agreement]`) Program agreements can have distribution agreements associated with them.

author = None
(`User|None`) Reference to the user who created the version.

created = None
(`datetime.datetime`) Date of creation of the agreement.

description = None
(str) Agreement details (Markdown).

link = None
(str) Url to the document.

marketplace = None
(*Marketplace* | None) Reference to marketplace object (for distribution agreement).

name = None
(str) Name of Agreement.

owner = None
(*Company*) Reference to the owner account object.

parent = None
(*Agreement* | None) Reference to the parent program agreement (for distribution agreement).

stats = None
(*AgreementStats* | None) Agreement stats.

title = None
(str) Title of the agreement.

type = None
(str) Type of the agreement. One of: distribution, program, service.

updated = None
(datetime.datetime) Date of the update of the agreement. It can be creation of the new version, change of the field, etc. (any change).

version = None
(int) Chronological number of the version.

version_contracts = None
(int) Number of contracts this version has.

version_created = None
(datetime.datetime) Date of the creation of the version.

class `connect.models.AgreementStats` (**kwargs)
Agreement stats.

contracts = None
(int|None) Number of contracts this agreement has.

versions = None
(int) Number of versions in the agreement.

class `connect.models.Anniversary` (**kwargs)
An Anniversary object.

day = None
(str) Day of the anniversary.

month = None
(str) Month of the anniversary.

class `connect.models.AssetRequest` (**kwargs)
Represents a request for the `connect.resource.FulfillmentAutomation` resource.

activation_key = None
(str) Activation key content for activating the subscription on vendor portal. This markdown formatted message is sent to customer.

asset = None

(*Asset*) Asset object.

assignee = None

(*User* | None) Details of the user assigned to the request.

changed_items

Returns Changed items.

Return type List[*Item*]

contract = None

(*Contract*) Contract object.

created = None

(datetime.datetime) Date of request creation.

get_conversation (*config=None*)

Parameters **config** (*Config*) – Configuration, or None to use the environment config (default).

Returns The conversation for this request, or None if there is none.

Return type Conversation|None

marketplace = None

(*Marketplace*) Marketplace object.

needs_migration (*migration_key='migration_info'*)

Indicates whether the request contains data to be migrated from a legacy product. Migration is performed by an external service. All you have to do for a request that needs migration is to skip processing by raising a *connect.exceptions.SkipRequest* exception.

Parameters **migration_key** (*str*) – The name of the parameter that contains the migration data (optional; default value is *migration_info*).

Returns Whether the request needs migrating.

Return type bool

new_items

Returns New items.

Return type List[*Item*]

note = None

(str) Details of note.

params_form_url = None

(str) URL for customer/reseller/provider for modifying param value based on vendor's feedback.

reason = None

(str) Fail reason in case of status of request is failed.

removed_items

Returns Removed items.

Return type List[*Item*]

status = None

(str) Status of request. One of:

- pending

- inquiring
- failed
- approved

Valid status changes:

- pending -> inquiring
- pending -> failed
- pending -> approved
- inquiring -> failed
- inquiring -> approved
- inquiring -> pending

type = None

(str) Asset status. See *Asset* class for details.

updated = None

(datetime.datetime) Date of last request modification.

class `connect.models.Asset` (**kwargs)

Represents a saleable item that can be provided/distributed in terms of one purchase.

These assets can be requested using `connect.resource.FulfillmentAutomation` resource.

An asset is characterized by the following:

- Every asset reflects some purchase (somebody purchases either a service or a good).
- Purchase action can be reverted (canceled) or terminated when terms of purchase are expired, see full state diagram on FIG.5
- Asset can be subscription-based (when customer pay for usage in some time terms) or one-time based.
- Matter of asset is defined as list of purchased items with purchased quantities (asset items).
- Item in asset may be either reservation-based, when customer decides how many items of SKU to be purchased or Pay-Per-User based when actual use of the SKU defines quantity for asset item.
- Asset may be modified using change requests: either set of items may be changed or quantities of reservation-based items may be changed.
- Some assets can be put into suspend state, when service is not actually provided and no charges happened.
- Assets also may be parametrized by one or more parameters which are differentiate one asset from another.

configuration = None

(*Configuration*) List of Product and Marketplace Configuration Phase Parameter Context-Bound Object.

connection = None

(*Connection*) Connection object.

contract = None

(*Contract*) Contract Object reference.

events = None

(*Events*) Events occurred on this asset.

external_id = None

(str) Identification for asset object on eCommerce.

external_name = None
(str|None) Name of asset.

external_uid = None
(str|None) Id of asset in eCommerce system.

get_item_by_global_id (*global_id*)
Get an item of the asset.

Parameters **global_id** (*str*) – Global id of the item to get.

Returns The item with the given global id, or *None* if it was not found.

Return type *Item* | *None*

get_item_by_id (*item_id*)
Get an item of the asset.

Parameters **item_id** (*str*) – Id of the item to get.

Returns The item with the given id, or *None* if it was not found.

Return type *Item* | *None*

get_item_by_mpn (*mpn*)
Get an item of the asset.

Parameters **mpn** (*str*) – MPN of the item to get.

Returns The item with the given MPN, or *None* if it was not found.

Return type *Item* | *None*

get_param_by_id (*param_id*)
Get a parameter of the asset.

Parameters **param_id** (*str*) – Id of the the parameter to get.

Returns The parameter with the given id, or *None* if it was not found.

Return type *Param* | *None*

get_requests (*config=None*)
Get the requests for this asset.

Parameters **config** (*Config*) – Config object or *None* to use environment config (default).

Returns The requests for this asset.

Return type List[*Fulfillment*]

items = None
(List[*Item*]) List of asset product items.

marketplace = None
(*Marketplace*) Marketplace Object reference.

params = None
(List[*Param*]) List of product parameter objects.

product = None
(*Product*) Product object reference.

status = None
Assets may have one of the following statuses:

- new: First purchase requested.

- processing: Until first purchase request is either completed or rejected.
- active: After the first purchase request is completed. NOTE: Asset stays active regardless of any other requests except cancel.
- rejected: Asset becomes rejected once the first purchase request is rejected.
- terminated: Asset becomes terminated once the 'cancel' request type is fulfilled.
- suspended: Asset becomes suspended once 'suspend' request type is fulfilled.

tiers = None
(*TierAccounts*) Supply chain accounts.

class `connect.models.Attributes` (**kwargs)
Attributes object.

provider = None
(obj) Attributes Provider.

vendor = None
(obj) Attributes Vendor.

class `connect.models.BaseModel` (**kwargs)
Base class of all models.

All the arguments provided on creation of the model are injected as attributes on the object.

classmethod `deserialize` (*json_str*)
Deserialize a string containing JSON data into a model.

Parameters `json_str` (*str*) – String containing the JSON data to be deserialized.

Returns An instance of the same class as the receiver of the call, or a list of instances.

Return type Anylist[Any]

Raises **TypeError** – Raised if the data cannot be deserialized.

classmethod `deserialize_json` (*json_data*)
Deserialize JSON data into a model.

Parameters `json_data` (*dict/list*) – JSON list or dictionary to be deserialized.

Returns An instance of the same class as the receiver of the call, or a list of instances.

Return type Anylist[Any]

Raises **TypeError** – Raised if the data cannot be deserialized.

id = None
(str) Globally unique id.

json
Returns The JSON representation of the model.
Return type dictlist

class `connect.models.Billing` (**kwargs)
Billing object.

anniversary = None
(*Anniversary*) Anniversary.

next_date = None
(str) Next date of the billing.

period = None
(*Period*) Period of the billing.

stats = None
(*Stats*) BillingStats of companySchema.

class connect.models.**BillingRequest** (**kwargs)
BillingRequest object.

asset = None
(object) Billing Request Asset.

attributes = None
(object) Billing Request Attributes.

events = None
(object) Billing Request Events.

item = None
(object) Billing Request Item.

period = None
(object) Billing Request Period.

type = None
(vendor|provider) Billing Request type.

class connect.models.**Company** (**kwargs)
Represents a company within the platform.

count = None
(integer) Count.

last_request = None
(*LastRequest*) Last Request of companySchema.

name = None
(str) Company name.

class connect.models.**Configuration** (**kwargs)
Configuration Phase Parameter Context-Bound Data Object.

To be used in parameter contexts:

- Asset.
- Fulfillment Request.
- TierConfig.
- TierConfig Requests.

get_param_by_id (*param_id*)
Get a parameter of the configuration.

Parameters **param_id** (*str*) – Id of the the parameter to get.

Returns The parameter with the given id, or None if it was not found.

Return type *Param* | None

params = None
(List[*Param*])

```

class connect.models.Connection (**kwargs)
    Represents a communication channel which provides the ability to order products within particular hub.

    Standalone connection is required for each product and for each provider account.

    created_at = None
        (datetime.datetime) Creation date.

    hub = None
        (Hub) Hub Reference.

    product = None
        (Product) Product Reference.

    provider = None
        (Company) Provider Account Reference.

    status = None
        (str) Status.

    type = None
        (str) Type of connection.

    vendor = None
        (Company) Vendor Account Reference.

class connect.models.Constraints (**kwargs)
    Parameter constraints.

    choices = None
        (List[ValueChoice]) Parameter value choices.

    hidden = None
        (bool) Is the parameter hidden?

    max_length = None
        (integer) Only for password type

    min_length = None
        (integer) Only for password type

    reconciliation = None
        (bool) True if vendor has marked parameters as for reconciliation purposes

    required = None
        (bool) Is the parameter required?

    unique = None
        (bool) Is the constraint unique?

class connect.models.Contact (**kwargs)
    Person of contact.

    email = None
        (str) Email address.

    first_name = None
        (str|None) First name.

    last_name = None
        (str|None) Last name.

    phone_number = None
        (PhoneNumber) Phone number.

```

class `connect.models.ContactInfo` (**kwargs)

Represents the information of a contact.

address_line1 = None

(str) Street address, first line.

address_line2 = None

(str|None) Street address, second line.

city = None

(str) City name.

contact = None

(*Contact*) Person of contact.

country = None

(str) Country code.

postal_code = None

(str) Postal ZIP code.

state = None

(str) State name.

class `connect.models.Contract` (**kwargs)

Contract object.

activation = None

(*Activation*) Activation information.

agreement = None

(*Agreement*) Reference object to the agreement.

created = None

(datetime.datetime) Contract creation date.

creator = None

(*User*) Reference object to the creator.

enrolled = None

(datetime.datetime|None) Date when contract was enrolled.

marketplace = None

(*Marketplace* | None) Reference object to the agreement marketplace.

name = None

(str) Contract name.

owner = None

(*Company* | None) Reference object to the owner company.

signee = None

(*User* | None) Reference object to the user of the owner company, who signed the contract.

status = None

(str) Contract Status. One of: enrolling, pending, active, terminated, rejected

type = None

(str) Type of the contract (same as agreement type). One of: distribution, program, service.

updated = None

(datetime.datetime) Date of contract status update.

version = None
(int) Version of the contract (same as associated agreement version).

version_created = None
(datetime.datetime) Contract version creation date.

class `connect.models.Country` (**kwargs)
Country data.

icon = None
(str) Icon path.

name = None
(str) Country name.

zone = None
(str) Geographical zone.

class `connect.models.Conversation` (**kwargs)
Conversation.

add_message (*message*, *config=None*)
Adds a message to the conversation.

Parameters

- **message** (*str*) – Message to add.
- **config** (*Config*) – Configuration, or None to use the environment config (default).

Returns The added message.

Return type *ConversationMessage*

Raises **TypeError** – Raised if the message cannot be deserialized.

created = None
(datetime.datetime) Date of the Conversation creation.

creator = None
(*User*) Creator of the conversation.

instance_id = None
(str) The id of object based on which discussion is made, e.g. listing request. It can be any object.

messages = None
(List[*ConversationMessage*]) List of *ConversationMessage* objects.

topic = None
(str) Conversation topic.

class `connect.models.ConversationMessage` (**kwargs)
Message in a *Conversation*.

conversation = None
(str) Primary ID of Conversation object.

created = None
(datetime.datetime) Date of the Message creation.

creator = None
(*User*) *User* that created the message.

text = None
(str) Actual message.

class `connect.models.CustomerUiSettings` (**kwargs)
Customer Ui Settings for a product.

description = None
(str) Description.

documents = None
(List[*Document*]) Documents.

download_links = None
(List[*DownloadLink*]) Download links.

getting_started = None
(str) Getting started.

class `connect.models.Document` (**kwargs)
Document for a product.

title = None
(str) Document title.

url = None
(str) Document URL.

class `connect.models.DownloadLink` (**kwargs)
Download link for a product.

title = None
(str) Link title.

url = None
(str) Link URL.

visible_for = None
(str) Link visibility. One of: admin, user.

class `connect.models.Event` (**kwargs)
Represents the date and user that caused an event.

at = None
(datetime.datetime|None) Date when the event occurred.

by = None
(*User*) User that caused the event.

class `connect.models.Events` (**kwargs)
Represents a set of events that can take place on an object.

accepted = None
(*EventInfo*) Accept event.

approved = None
(*EventInfo*) Approve event.

closed = None
(*EventInfo*) Close event.

created = None
(*EventInfo*) Creation event.

inquired = None
(*EventInfo*) Inquire event.


```

pending = None
    (EventInfo) Pending event.

rejected = None
    (EventInfo) Reject event.

submitted = None
    (EventInfo) Submit event.

updated = None
    (EventInfo) Update event.

uploaded = None
    (EventInfo) Uploaded event.

validated = None
    (EventInfo) Validation event.

class connect.models.ExtIdHub (**kwargs)
    Associates a Hub with an external id.

    external_id = None
        (str) External id.

    hub = None
        (Hub) Hub.

class connect.models.Fulfillment (*args, **kwargs)
    Represents a request for the connect.resource.FulfillmentAutomation resource.

class connect.models.Hub (**kwargs)
    A Hub.

    company = None
        (Company) Reference to the company the hub belongs to.

    description = None
        (str|None) Hub description (Markdown text).

    events = None
        (Events) Events occurred on Hub.

    instance = None
        (HubInstance) Hub instance.

    name = None
        (str) Hub name.

    stats = None
        (HubStats) Hub stats.

class connect.models.HubInstance (**kwargs)
    An instance of a hub.

    type = None
        (str) E-Commerce system type.

class connect.models.HubStats (**kwargs)
    Hub stats.

    connections = None
        (int) Number of connections active for this Hub.

```

marketplaces = None
(int) Number of marketplaces for this Hub.

class `connect.models.Item` (**kwargs)
A product item.

display_name = None
(str) Display name.

get_param_by_id (*param_id*)
Get a parameter of the item.

Parameters *param_id* (*str*) – Id of the the parameter to get.

Returns The parameter with the given id, or None if it was not found.

Return type *Param* | None

global_id = None
(str) Global id.

item_type = None
(str) Item type.

mpn = None
(str) Item manufacture part number.

name = None
(str) Name.

old_quantity = None
(int|float|None) Previous value of quantity.

params = None
(List[*Param* | None] List of Item and Item x Marketplace Configuration Phase Parameter Context-Bound Object

period = None
(str) Period.

quantity = None
(int|float) Number of items of the type in the asset (-1 if unlimited)

renewal = None
(*Renewal* | None) Parameters of renewal request (empty for all other types).

type = None
(str) Type.

class `connect.models.LastRequest` (**kwargs)
Last Request object.

type = None
(str) Type of last request.

class `connect.models.Marketplace` (**kwargs)

An object containing Distribution agreements with exact Hubs, enriched with additional information on details about the relation.

A Marketplace is a way to list Products to specified regions (based on Distribution Agreements) and use specific Hubs to provision incoming Fulfillment requests.

active_contracts = None
(int) How many active contracts were signed on the Marketplace.

countries = None

List[*Country*] List of country objects associated with marketplace.

description = None

(str) Markdown text describing the marketplace.

hubs = None

(List[*ExtIdHub*]) List of account-hub relations associated with the Marketplace object.

icon = None

(str) Image identifying Marketplace object uploaded by user.

name = None

(str) Marketplace title, unique for an account.

owner = None

(*Company*) Provider account - the object owner.

sourcing = None

(bool) Is marketplace available for sourcing.

zone = None

(str) Zone where the marketplace is located, there can be following zones: AF, NA, OC, AS, EU, SA (It is continents).

class `connect.models.Param` (**kwargs)

Parameters are used in product and asset definitions.

constraints = None

(*Constraints* | None) Parameter constraints.

description = None

(str) Description of parameter.

events = None

(*Events* | None) Events.

marketplace = None

(*Marketplace* | None) Marketplace.

name = None

(str) Name of parameter.

phase = None

(str|None) Param phase.

reconciliation = None

(bool|None) Is Parameter used as reconciliation one from vendor invoices

scope = None

(str|None) Scope of parameter.

title = None

(str|None) Title for parameter.

type = None

(str) Type of parameter.

value = None

(str|None) Value of parameter.

value_choice = None

(List[str]|None) Available choices for parameter.

value_choices = None
(List[str]|None) Available dropdown choices for parameter.

value_error = None
(str|None) Error indicated for parameter.

class `connect.models.Period` (**kwargs)
Period object.

delta = None
(string) Period Delta.

period_from = None
(datetime.date) Period From.

period_to = None
(datetime.date) Period To.

uom = None
(string) Period uom.

class `connect.models.PhoneNumber` (**kwargs)
Phone number.

area_code = None
(str|None) Area code.

country_code = None
(str|None) Country code.

extension = None
(str|None) Phone extension.

phone_number = None
(str|None) Phone number.

class `connect.models.Product` (**kwargs)

Represents basic marketing information about salable items, parameters, configurations, latest published version and connections.

It contains basic product information like name, description and logo, along with the latest published version details. So in a single point we can say a single product object always represent the latest published version of that product.

category = None
(*ProductCategory* | None) Reference to ProductCategory Object.

configurations = None
(*ProductConfiguration*) Product configuration.

customer_ui_settings = None
(*CustomerUiSettings*) Customer Ui Settings.

detailed_description = None
(str) Detailed description of product.

get_product_configurations (*filters=None, config=None*)

Parameters

- **filters** (*dict/Query*) – Filters for the requests. Supported filters are: - parameter.id-parameter.title-parameter.scope-marketplace.id - marketplace.name - item.id - item.name - value

- **config** (*Config*) – Configuration to use, or None for environment config.

Returns A list with the product configuration parameter data.

Return type List[*ProductConfigurationParameter*]

get_templates (*config=None*)

Parameters **config** (*Config*) – Configuration to use, or None for environment config.

Returns List of all templates associated with the product.

Return type List[*Template*]

icon = None

(str) Product icon URI.

latest = None

(bool|None) true if version is latest or for master versions without versions, false otherwise.

name = None

(str) Product name.

owner = None

(*Company* | None)

published_at = None

(datetime.datetime) Date of publishing.

short_description = None

(str) Short description of product.

stats = None

(:py:class:“.ProductStats) Statistics of product use, depends on account of callee.

status = None

(str) Product status.

version = None

(int) Version of product.

class `connect.models.ProductCategory` (**kwargs)

Represents a product category.

children = None

(List[*ProductCategory*] | None) List of children categories.

family = None

(*ProductFamily* | None) Product family.

name = None

(str) Category name.

parent = None

(*ProductCategory* | None) Reference to parent category.

class `connect.models.ProductConfiguration` (**kwargs)

Product configurations.

requires_reseller_information = None

(bool) Does the product require reseller information?

suspend_resume_supported = None

(bool) Is suspend and resume supported for the product?

class `connect.models.ProductConfigurationParameter` (**kwargs)
Representation of Configuration Phase Parameter (CPP) Data object

constraints = None
(*Constraints*) Constraints.

events = None
(*Events*) Product events.

item = None
(*Item* | None) Reference to Item.

marketplace = None
(*Marketplace* | None) Reference to Marketplace.

parameter = None
(*Param*) Full representation of parameter.

value = None
(str | None) Configuration parameter value.

class `connect.models.ProductFamily` (**kwargs)
Represents a family of products

name = None
(str) Family name.

class `connect.models.ProductStats` (**kwargs)
Statistics of product use.

agreements = None
(*ProductStatsInfo*) Agreements related to the product.

contracts = None
(*ProductStatsInfo*) Contracts related to the product.

listing = None
(int) Number of listings (direct use of product by provider).

class `connect.models.ProductStatsInfo` (**kwargs)

distribution = None
(int) Number of distributions related to the product.

sourcing = None
(int) Number of sourcings related to the product.

class `connect.models.RecurringAsset` (**kwargs)
RecurringAsset object.

billing = None
(object) Billing Request billing.

connection = None
(object) Billing Request connection.

contract = None
(object) Billing Request Contract.

events = None
(object) Billing Request Events.

```
external_id = None
    (str) External Id.

external_uuid = None
    (str) External uuid.

items = None
    (object) Billing Request Item.

marketplace = None
    (object) Billing Request marketplace.

params = None
    (object) Billing Request Params.

product = None
    (object) product.

status = None
    (vendor|provider) Billing Request status.

tiers = None
    (object) Billing Request tiers.

class connect.models.Renewal (**kwargs)
    Item renewal data.

from_ = None
    (datetime.datetime) Date of renewal beginning.

period_delta = None
    (int) Size of renewal period.

period_uom = None
    (str) Unit of measure for renewal period. One of: year, month, day, hour.

to = None
    (datetime.datetime) Date of renewal end.

class connect.models.ServerErrorResponse (**kwargs)
    Server response when an error occurs.

error_code = None
    (str) Error code.

errors = None
    (List[str]) List of errors.

params = None
    (dict) Error params.

class connect.models.Stat (**kwargs)
    Stats object.

count = None
    (Int) Count.

last_request = None
    (LastRequest) Last Request.

class connect.models.Stats (**kwargs)
    Stats object.
```

```
provider = None
    (Company) Provider.

vendor = None
    (Company) Vendor.

class connect.models.Template (**kwargs)
    Tier Template

body = None
    (str) Template body.

name = None
    (str) Template name.

representation = None
    (str) Template representation.

class connect.models.TierAccount (**kwargs)
    Tier account.

class connect.models.TierAccountRequest (**kwargs)
    Tier account request.

class connect.models.TierAccounts (**kwargs)
    TierAccounts object.

customer = None
    (TierAccount) Customer Level TierAccount Object.

tier1 = None
    (TierAccount) Level 1 TierAccount Object.

tier2 = None
    (TierAccount | None) Level 2 TierAccount Object.

class connect.models.TierConfig (**kwargs)
    Full representation of Tier object.

account = None
    (TierAccount) Full tier account representation (same as in Asset).

configuration = None
    (Configuration) List of Product and Marketplace Configuration Phase Parameter Context-Bound Object.

connection = None
    (Connection) Reference to Connection Object.

contract = None
    (Contract) Contract Object reference.

events = None
    (Events | None) Tier Config events.

classmethod get (account_id, product_id, config=None)
    Gets the specified tier config data. For example, to get Tier 1 configuration data for one request we can do:

    TierConfig.get(request.asset.tiers.tier1.id, request.asset.product.id)
```

Parameters

- **account_id** (*str*) – Account Id of the requested Tier Config (id with TA prefix).

- **product_id** (*str*) – Id of the product.
- **config** (*Config*) – Config to use, or *None* to use environment config (default).

Returns The requested Tier Config, or *None* if it was not found.

Return type *Optional[TierConfig]*

get_param_by_id (*id_*)

Get a Tier Config parameter.

Parameters **id** (*str*) – Parameter id.

Returns The requested parameter, or *None* if it was not found.

Return type *Param*

marketplace = None

(*Marketplace*) Marketplace Object reference.

name = None

(*str*) Tier configuration of account.name.

open_request = None

(*BaseModel* | *None*) Reference to TCR.

params = None

(*List[Param]*) List of TC parameter data objects as in Asset Object extended with unfilled parameters from product.

product = None

(*Product*) Reference object to product (application).

status = None

(*str*) TierConfig status.

template = None

(*Template*) Template Object.

tier_level = None

(*int*) Tier level for product from customer perspective.

class `connect.models.TierConfigRequest` (***kwargs*)

account = None

(*TierAccount*) Reference object to TierAccount.

activation = None

(*Activation* | *None*) Activation object. This is created only if TCR has ordering parameters and seen in inquiring state of the TCR.

assignee = None

(*User* | *None*) User assigned to this TCR.

configuration = None

(*TierConfig*) Full representation of TierConfig Object.

contract = None

(*Contract* | *None*) TierConfig contract.

environment = None

(*str*) TCR environment (test, prod or preview)

events = None
(*Events* | None) Tier Config request Events.

get_param_by_id (*id_*)
Get a Tier Config Request parameter.

Parameters *id* (*str*) – Parameter id.

Returns The requested parameter, or *None* if it was not found.

Return type *Param*

marketplace = None
(*Marketplace* | None) TierConfig marketplace.

notes = None
(*str*) TCR pending notes. Notes can be modified only in Pending state.

params = None
(*List[Param]*) List of parameter data objects as in Asset Object. Params can be modified only in Pending state.

parent_configuration = None
(*TierConfig* | None) Full representation of parent TierConfig.

product = None
(*Product*) Reference object to product (application).

reason = None
(*str*|None) Failing reason. This is filled only if TCR is failed.

status = None
(*str*) TCR current status. One of: *tiers_setup*, *pending*, *inquiring*, *approved*, *failed*.

template = None
(*Template* | None) Template Object. This is filled only if TCR is approved.

tier_level = None
(*int*) Tier level for product from customer perspective (1 or 2).

tiers = None
(*TierAccounts* | None) TierConfig tier accounts.

type = None
(*str*) TCR type. One of: *setup*, *update*.

class `connect.models.UsageFile` (***kwargs*)
Usage File Object.

acceptance_note = None
(*str*) Note provided by the provider in case of acceptance of the usage file.

contract = None
(*Contract*) Reference on Contract Object.

created_at = None
(*str*) Date of the creation of the UsageFile.

created_by = None
(*str*) User ID who have created this UsageFile.

currency = None
(*str*) Currency of the amount included in usage file.

description = None

(str) Vendor can provide a description value in this field to describe the file content.

environment = None

(str) Environment.

error_details = None

(str) In case of invalid file, this field will contain errors related to the file.

events = None

(*Events*) Events occurred on file.

external_id = None

(str) External ID of the file.

marketplace = None

(*Marketplace*) Reference on Marketplace Object.

name = None

(str) Name of the Usage file object.

note = None

(str) Vendor can put a note which can be refer later for some extra information.

period_from = None

(str) Date & time from which usage records are considered in this usage file.

period_to = None

(str) Date & time from which usage records are considered in this usage file.

processed_file_uri = None

(str) Google Storage shared location of the generated file after processing uploaded file. Only available in GET API and not included in list API (sharing timeout 30 sec).

product = None

(*Product*) Reference on Product Object.

provider = None

(*Company*) Reference object to the provider company.

records = None

(*UsageRecords*) UsageRecords Object.

rejection_note = None

(str) Note provider by the provider in case of rejection of the usage file.

schema = None

(str) Usage Scheme used for the usage file.

stats = None

(*UsageStats*) UsageStats Object.

status = None

(str) One of: draft, uploading, uploaded, processing, invalid, ready, rejected, pending, accepted, closed.

usage_file_uri = None

(str) Google Storage shared location of the upload file. Only available in GET API and not included in list API (sharing timeout 600 sec).

vendor = None

(*Company*) Reference object to the vendor company.

class `connect.models.UsageListing` (**kwargs)

Usage Listing Object.

contract = None
(*Contract*) Contract Object.

created = None
(str) Creation time.

product = None
(*Product*) Product Object.

provider = None
(*Company*) Provider Object.

status = None
(str) Status.

vendor = None
(*Company*) Vendor Object.

class `connect.models.UsageRecord(**kwargs)`
Usage Record Object.

amount = None
(float) Amount.

asset_recon_id = None
(str) Asset recon Id.

asset_search_criteria = None
(str) Asset search criteria.

asset_search_value = None
(str) Asset search value.

category_id = None
(str) Category Id.

end_time_utc = None
(str) End Time in UTC.

item_name = None
(str) Item name.

item_npm = None
(str) Item npm.

item_precision = None
(str) Item precision.

item_search_criteria = None
(str) Item search criteria.

item_search_value = None
(str) Item search value.

item_unit = None
(str) Item unit.

quantity = None
(int) Quantity.

start_time_utc = None
(str) Start Time in UTC.

```

tier = None
    (str) Tier.

usage_record_id = None
    (str) Usage record id.

usage_record_note = None
    (str) Usage record note.

class connect.models.UsageRecords (**kwargs)
    Usage Records Object.

invalid = None
    (int) Invalid.

valid = None
    (int) Valid.

class connect.models.UsageStats (**kwargs)
    Usage Stats object.

accepted = None
    (Int) Accepted.

closed = None
    (Int) Closed.

pending = None
    (Int) Pending.

uploaded = None
    (Int) Uploaded.

validated = None
    (Int) Validated.

class connect.models.User (**kwargs)
    Represents a user within the platform.

email = None
    (str) User email.

name = None
    (str) User name.

class connect.models.ValueChoice (**kwargs)
    A value choice for a parameter.

label = None
    (str) Label.

value = None
    (str) Value.

```

2.2.4 resources

```

class connect.resources.Directory (config=None)
    Allows listing and obtaining several types of objects.

    Parameters config (Config) – Config object or None to use environment config (default).

get_asset (asset_id)
    Returns the asset with the given id.

```

Parameters `asset_id (str)` – The id of the asset.

Returns The asset with the given id, or `None` if such asset does not exist.

Return type `Asset|None`

get_marketplace (`marketplace_id`)

Obtains Marketplace object given its ID.

Parameters `marketplace_id (str)` – The id of the marketplace.

Returns The marketplace with the given id, or `None` if such marketplace does not exist.

Return type `Marketplace|None`

get_product (`product_id`)

Returns the product with the given id.

Parameters `product_id (str)` – The id of the product.

Returns The product with the given id, or `None` if such product does not exist.

Return type `Product|None`

get_tier_config (`tier_config_id`)

Returns the tier config with the given id.

Parameters `tier_config_id (str)` – The id of the tier config.

Returns The Tier Config with the given id, or `None` if such Tier Config does not exist.

Return type `TierConfig|None`

list_assets (`filters=None`)

List the assets.

Parameters `filters (dict|Query)` – Filters to pass to the request.

Returns A list with the assets that match the given filters.

Return type `list[Asset]`

list_marketplaces (`filters=None`)

List the marketplaces.

Parameters `filters (dict|Query)` – Filters to pass to the request.

Returns List of marketplaces matching given filters.

Return type `list[Marketplace]`

list_products (`filters=None`)

List the products.

Parameters `filters (dict|Query)` – Filters to pass to the request.

Returns A list with all products.

Return type `list[Product]`

list_tier_configs (`filters=None`)

List the tier configs.

Parameters `Any` `filters ((dict[str,])` – Filters to pass to the request.

Returns A list with the tier configs that match the given filters.

Return type `list[TierConfig]`

class `connect.resources.FulfillmentAutomation` (*config=None*)

This is the automation engine for the Fulfillment API. If you want to process fulfillment requests, subclass this and implement the `process_request` method, which receives a `connect.models.FulfillmentRequest` as argument and must return an `connect.models.ActivationTemplateResponse` or `connect.models.ActivationTileResponse` object in case the request has to be approved.

In other case, you must raise one of these exceptions:

- `connect.exceptions.InquireRequest`: Inquire for more information.
- `connect.exceptions.FailRequest`: Causes the request to fail.
- `connect.exceptions.SkipRequest`: Skips processing the request.

Create an instance of your subclass and call its `process` method to begin processing.

For an example on how to use this class, see [Processing Fulfillment Requests](#).

create_request (*request*)

Creates a new request. Using this method requires a provider token used as `api_key` in the Config.

Parameters `request` (`Fulfillment`) –

Returns The created request.

Return type `Fulfillment`

filters (*status='pending', **kwargs*)

Returns the default set of filters for Fulfillment request, plus any others that you might specify. The allowed filters are:

- `status`
- `created`
- `id` (List support)
- `type` (`purchase|renew|change|cancel`)
- `asset.id` (`asset_id`) - (List support)
- `asset.product.id` (`product_id`)
- `asset.product.name` - (List support)
- `asset.hub.id`
- `asset.connection.hub.name` - (List support)
- `asset.connection.provider.id`
- `asset.connection.provider.name` - (List support)
- `asset.connection.vendor.name` - (List support)
- `asset.tiers.customer.id` (Customer ID)
- `asset.tiers.tier1.id`
- `asset.tiers.tier2.id`
- `asset.connection.type` (`test|production|preview`)

Parameters

- **status** (*str*) – Status of the requests. Default: `'pending'`.
- **kwargs** (*dict[str, Any]*) – Additional filters to add to the default ones.

Returns The set of filters for this resource.

Return type dict[str,Any]

get_tier_config (*tier_id*, *product_id*)

Gets the specified tier config data. For example, to get Tier 1 configuration data for one request, within the FulfillmentAutomation instance, we can do:

```
self.get_tier_config(request.asset.tiers.tier1.id, request.asset.product.id)
```

Parameters

- **tier_id** (*str*) – Account Id of the requested Tier Config (id with TA prefix).
- **product_id** (*str*) – Id of the product.

Returns The requested Tier Config, or None if it was not found.

Return type Optional[TierConfig]

Deprecated since version 16.0: Use TierConfig.get instead.

model_class

alias of connect.models.fulfillment.Fulfillment

update_parameters (*pk*, *params*)

Sends a list of Param objects to Connect for updating.

Parameters

- **pk** (*str*) – Id of the request.
- **params** (*list* [Param]) – List of parameters to update.

Returns The server response.

Return type str

class connect.resources.**MarketplaceResource** (*config=None*)

Resource to work with `connect.models.Marketplace` models. :param Config config: Config object or None to use environment config (default).

model_class

alias of connect.models.marketplace.Marketplace

class connect.resources.**TemplateResource** (*config=None*)

Template Resource.

get (*pk*)

Get an activation template.

Parameters **pk** (*str*) – Primary key of the template to obtain.

Returns ActivationTemplateResponse object with template contents.

Return type *ActivationTemplateResponse*

list (*product_id*)

List an activation template. :param str product_id: Primary key of the product to search for. :return: response object with templates contents.

render (*pk*, *request_id*)

Get an activation tile.

Parameters

- **pk** (*str*) – Primary key of the template to obtain.
- **request_id** (*str*) – Id of the associated request.

Returns ActivationTileResponse object with tile contents.

Return type *ActivationTileResponse*

class `connect.resources.TierConfigAutomation` (*config=None*)

This is the automation engine for the Tier Config Request API. If you want to process Tier Config requests, subclass this and implement the `process_request` method, which receives a `connect.models.TierConfigRequest` request as argument and must return an `connect.models.ActivationTemplateResponse` or `connect.models.ActivationTileResponse` object in case the request has to be approved.

In other case, you must raise one of these exceptions:

- `connect.exceptions.InquireRequest`: Inquire for more information.
- `connect.exceptions.FailRequest`: Causes the request to fail.
- `connect.exceptions.SkipRequest`: Skips processing the request.

Create an instance of your subclass and call its `process` method to begin processing.

For an example on how to use this class, see [Processing Tier Config Requests](#).

filters (*status='pending', **kwargs*)

Returns the default set of filters for Tier Config request, plus any others that you might specify. The allowed filters are:

- type
- status
- id
- configuration.id
- configuration.tier_level
- configuration.account.id
- configuration.product.id
- assignee.id
- unassigned (bool)
- configuration.account.external_uid

Parameters

- **status** (*str*) – Status of the requests. Default: 'pending'.
- **kwargs** (*dict[str, Any]*) – Additional filters to add to the default ones.

Returns The set of filters for this resource.

Return type `dict[str, Any]`

model_class

alias of `connect.models.tier_config_request.TierConfigRequest`

update_parameters

 (*pk, params*)

Sends a list of Param objects to Connect for updating.

Parameters

- **pk** (*str*) – Id of the request.
- **params** (*list [Param]*) – List of parameters to update.

Returns The server response.

Return type str

class connect.resources.**UsageAutomation** (*config=None*)
Automates reporting of Usage Files.

For an example on how to use this class, see [Reporting Usage Files](#).

filters (*status='listed', **kwargs*)

Parameters

- **status** (*str*) – Status of the requests. Default: 'listed'.
- **kwargs** (*dict [str, Any]*) – Additional filters to add to the default ones.

Returns The set of filters for this resource.

Return type dict[str,Any]

get_usage_template (*product*)

Returns the template file contents for a specified product.

Parameters **product** (*Product*) – Specific product.

Returns The template file contents.

Return type bytes

Raises *FileRetrievalError* – Raised if the file contents could not be retrieved.

model_class

alias of connect.models.usage_file.UsageFile

submit_usage (*usage_file, usage_records*)

Submit a usage file.

Parameters

- **usage_file** (*UsageFile*) – Usage file.
- **usage_records** (*list [UsageRecord]*) – Records.

Returns Usage file.

Return type *UsageFile*

Raises *FileCreationError* – Raised if creation or uploading of the file fails.

class connect.resources.**UsageFileAutomation** (*config=None*)
Automates workflow of Usage Files.

For an example on how to use this class, see [Workflow of Usage Files](#).

filters (*status='ready', **kwargs*)

Parameters

- **status** (*str*) – Status of the requests. Default: 'ready'.
- **kwargs** (*dict [str, Any]*) – Additional filters to add to the default ones.

Returns The set of filters for this resource.

Return type dict[str,Any]

model_class

alias of `connect.models.usage_file.UsageFile`

class `connect.resources.BillingRequest` (**kwargs)

BillingRequest object.

asset = None

(object) Billing Request Asset.

attributes = None

(object) Billing Request Attributes.

events = None

(object) Billing Request Events.

item = None

(object) Billing Request Item.

period = None

(object) Billing Request Period.

type = None

(vendor|provider) Billing Request type.

class `connect.resources.RecurringAsset` (**kwargs)

RecurringAsset object.

billing = None

(object) Billing Request billing.

connection = None

(object) Billing Request connection.

contract = None

(object) Billing Request Contract.

events = None

(object) Billing Request Events.

external_id = None

(str) External Id.

external_uuid = None

(str) External uuid.

items = None

(object) Billing Request Item.

marketplace = None

(object) Billing Request marketplace.

params = None

(object) Billing Request Params.

product = None

(object) product.

status = None

(vendor|provider) Billing Request status.

tiers = None

(object) Billing Request tiers.

class `connect.resources.AssetRequestResource` (*config=None*)

Asset Request Resource.

model_class

alias of `connect.models.asset_request.AssetRequest`

update_param_asset_request (*request_id, data, note*)

Update Asset Request param :param str id_request: Primary key of the request to update. :param str data: params to update.

```
{
    "params": [{"id": "PM-9861-7949-8492-0001", "value": "32323323"}]
}
```

Returns Asset Request Attributes Object.

2.2.5 rql

class `connect.rql.Query` (*properties=None*)

The Query class allows you to specify filters using the [Resource Query Language](#) syntax.

Parameters `properties` (*dict*) – Initial list of input properties

compile ()

Returns A string representation of the query.

Return type str

equal (*prop, value*)

Select objects with a property value equal to value.

Parameters

- **prop** (*str*) – Property.
- **value** (*str*) – Value.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

greater (*prop, value*)

Select objects with a property value greater than the value.

Parameters

- **prop** (*str*) – Property.
- **value** (*str*) – Value.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

greater_equal (*prop, value*)

Select objects with a property value equal or greater than the value.

Parameters

- **prop** (*str*) – Property.

- **value** (*str*) – Value.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

ilike (*prop, pattern*)

Same as like but case insensitive.

Parameters

- **prop** (*str*) – Property.
- **pattern** (*str*) – Pattern.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

in_ (*prop, values*)

Select objects where the specified property value is in the provided array.

Parameters

- **prop** (*str*) – Property
- **values** (*list*) – Values

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

lessor (*prop, value*)

Select objects with a property value less than the value.

Parameters

- **prop** (*str*) – Property.
- **value** (*str*) – Value.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

lessor_equal (*prop, value*)

Select objects with a property value equal or lesser than the value.

Parameters

- **prop** (*str*) – Property.
- **value** (*str*) – Value.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

like (*prop, pattern*)

Search for the specified pattern in the specified property. The function is similar to the SQL LIKE operator, though it uses the * wildcard instead of %. To specify in a pattern the * symbol itself, it must be percent-encoded, that is, you need to specify %2A instead of *, see the usage examples below. In addition, it is possible to use the ? wildcard in the pattern to specify that any symbol will be valid in this position.

Parameters

- **prop** (*str*) – Property.
- **pattern** (*str*) – Pattern.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

limit (*amount*)

Indicates the given number of objects from the start position.

Parameters **amount** (*int*) – Amount of objects to return.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

not_equal (*prop, value*)

Select objects with a property value not equal to value.

Parameters

- **prop** (*str*) – Property.
- **value** (*str*) – Value.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

offset (*page*)

Offset (page) to return on paged queries.

Parameters **page** (*int*) – Offset.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

order_by (*prop*)

Order list by given property.

Parameters **prop** (*str*) – Property.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

ordering (*props*)

Order list of objects by the given properties (unlimited number of properties). The list is ordered first by the first specified property, then by the second, and so on. The order is specified by the prefix: + ascending order, - descending.

Parameters **props** (*list*) – Properties.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

out (*prop, values*)

Select objects where the specified property value is not in the provided array.

Parameters

- **prop** (*str*) – Property
- **values** (*list*) – Values

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

select (*attributes*)

The function is applicable to a list of resources (hereafter base resources). It receives the list of attributes (up to 100 attributes) that can be primitive properties of the base resources, relation names, and relation names combined with properties of related resources. The output is the list of objects presenting the selected properties and related (linked) resources. Normally, when relations are selected, the base resource properties are also presented in the output.

Parameters **attributes** (*list*) – Attributes.

Returns The Query object to provide a fluent interface (chaining method calls).

Return type *Query*

CHAPTER 3

Indices and tables

- `genindex`
- `modindex`
- `search`

C

`connect.config`, 8
`connect.exceptions`, 9
`connect.models`, 10
`connect.resources`, 33
`connect.rql`, 40

A

acceptance_note (*connect.models.UsageFile attribute*), 30

accepted (*connect.models.Events attribute*), 20

accepted (*connect.models.UsageStats attribute*), 33

AcceptUsageFile, 9

account (*connect.models.TierConfig attribute*), 28

account (*connect.models.TierConfigRequest attribute*), 29

Activation (*class in connect.models*), 10

activation (*connect.models.Contract attribute*), 18

activation (*connect.models.TierConfigRequest attribute*), 29

activation_key (*connect.models.AssetRequest attribute*), 11

ActivationTemplateResponse (*class in connect.models*), 10

ActivationTileResponse (*class in connect.models*), 10

active (*connect.models.Agreement attribute*), 10

active_contracts (*connect.models.Marketplace attribute*), 22

add_message() (*connect.models.Conversation method*), 19

address_line1 (*connect.models.ContactInfo attribute*), 18

address_line2 (*connect.models.ContactInfo attribute*), 18

Agreement (*class in connect.models*), 10

agreement (*connect.models.Contract attribute*), 18

agreements (*connect.models.Agreement attribute*), 10

agreements (*connect.models.ProductStats attribute*), 26

AgreementStats (*class in connect.models*), 11

amount (*connect.models.UsageRecord attribute*), 32

Anniversary (*class in connect.models*), 11

anniversary (*connect.models.Billing attribute*), 15

api_key (*connect.config.Config attribute*), 8

api_url (*connect.config.Config attribute*), 8

approved (*connect.models.Events attribute*), 20

area_code (*connect.models.PhoneNumber attribute*), 24

Asset (*class in connect.models*), 13

asset (*connect.models.AssetRequest attribute*), 11

asset (*connect.models.BillingRequest attribute*), 16

asset (*connect.resources.BillingRequest attribute*), 39

asset_recon_id (*connect.models.UsageRecord attribute*), 32

asset_search_criteria (*connect.models.UsageRecord attribute*), 32

asset_search_value (*connect.models.UsageRecord attribute*), 32

AssetRequest (*class in connect.models*), 11

AssetRequestResource (*class in connect.resources*), 39

assignee (*connect.models.AssetRequest attribute*), 12

assignee (*connect.models.TierConfigRequest attribute*), 29

at (*connect.models.Event attribute*), 20

Attributes (*class in connect.models*), 15

attributes (*connect.models.BillingRequest attribute*), 16

attributes (*connect.resources.BillingRequest attribute*), 39

author (*connect.models.Agreement attribute*), 10

B

BaseModel (*class in connect.models*), 15

Billing (*class in connect.models*), 15

billing (*connect.models.RecurringAsset attribute*), 26

billing (*connect.resources.RecurringAsset attribute*), 39

BillingRequest (*class in connect.models*), 16

BillingRequest (*class in connect.resources*), 39

body (*connect.models.Template attribute*), 28

by (*connect.models.Event attribute*), 20

C

category (*connect.models.Product attribute*), 24

- category_id (*connect.models.UsageRecord attribute*), 32
 - changed_items (*connect.models.AssetRequest attribute*), 12
 - children (*connect.models.ProductCategory attribute*), 25
 - choices (*connect.models.Constraints attribute*), 17
 - city (*connect.models.ContactInfo attribute*), 18
 - closed (*connect.models.Events attribute*), 20
 - closed (*connect.models.UsageStats attribute*), 33
 - CloseUsageFile, 9
 - code (*connect.exceptions.Message attribute*), 9
 - Company (*class in connect.models*), 16
 - company (*connect.models.Hub attribute*), 21
 - compile() (*connect.rql.Query method*), 40
 - Config (*class in connect.config*), 8
 - Configuration (*class in connect.models*), 16
 - configuration (*connect.models.Asset attribute*), 13
 - configuration (*connect.models.TierConfig attribute*), 28
 - configuration (*connect.models.TierConfigRequest attribute*), 29
 - configurations (*connect.models.Product attribute*), 24
 - connect.config (*module*), 8
 - connect.exceptions (*module*), 9
 - connect.models (*module*), 10
 - connect.resources (*module*), 33
 - connect.rql (*module*), 40
 - Connection (*class in connect.models*), 16
 - connection (*connect.models.Asset attribute*), 13
 - connection (*connect.models.RecurringAsset attribute*), 26
 - connection (*connect.models.TierConfig attribute*), 28
 - connection (*connect.resources.RecurringAsset attribute*), 39
 - connections (*connect.models.HubStats attribute*), 21
 - Constraints (*class in connect.models*), 17
 - constraints (*connect.models.Param attribute*), 23
 - constraints (*connect.models.ProductConfigurationParameter attribute*), 26
 - Contact (*class in connect.models*), 17
 - contact (*connect.models.ContactInfo attribute*), 18
 - ContactInfo (*class in connect.models*), 17
 - Contract (*class in connect.models*), 18
 - contract (*connect.models.Asset attribute*), 13
 - contract (*connect.models.AssetRequest attribute*), 12
 - contract (*connect.models.RecurringAsset attribute*), 26
 - contract (*connect.models.TierConfig attribute*), 28
 - contract (*connect.models.TierConfigRequest attribute*), 29
 - contract (*connect.models.UsageFile attribute*), 30
 - contract (*connect.models.UsageListing attribute*), 31
 - contract (*connect.resources.RecurringAsset attribute*), 39
 - contracts (*connect.models.AgreementStats attribute*), 11
 - contracts (*connect.models.ProductStats attribute*), 26
 - Conversation (*class in connect.models*), 19
 - conversation (*connect.models.ConversationMessage attribute*), 19
 - ConversationMessage (*class in connect.models*), 19
 - count (*connect.models.Company attribute*), 16
 - count (*connect.models.Stat attribute*), 27
 - countries (*connect.models.Marketplace attribute*), 22
 - Country (*class in connect.models*), 19
 - country (*connect.models.ContactInfo attribute*), 18
 - country_code (*connect.models.PhoneNumber attribute*), 24
 - create_request() (*connect.resources.FulfillmentAutomation method*), 35
 - created (*connect.models.Agreement attribute*), 10
 - created (*connect.models.AssetRequest attribute*), 12
 - created (*connect.models.Contract attribute*), 18
 - created (*connect.models.Conversation attribute*), 19
 - created (*connect.models.ConversationMessage attribute*), 19
 - created (*connect.models.Events attribute*), 20
 - created (*connect.models.UsageListing attribute*), 32
 - created_at (*connect.models.Connection attribute*), 17
 - created_at (*connect.models.UsageFile attribute*), 30
 - created_by (*connect.models.UsageFile attribute*), 30
 - creator (*connect.models.Contract attribute*), 18
 - creator (*connect.models.Conversation attribute*), 19
 - creator (*connect.models.ConversationMessage attribute*), 19
 - currency (*connect.models.UsageFile attribute*), 30
 - customer (*connect.models.TierAccounts attribute*), 28
 - customer_ui_settings (*connect.models.Product attribute*), 24
 - CustomerUiSettings (*class in connect.models*), 19
- ## D
- date (*connect.models.Activation attribute*), 10
 - day (*connect.models.Anniversary attribute*), 11
 - DeleteUsageFile, 9
 - delta (*connect.models.Period attribute*), 24
 - description (*connect.models.Agreement attribute*), 10
 - description (*connect.models.CustomerUiSettings attribute*), 20
 - description (*connect.models.Hub attribute*), 21
 - description (*connect.models.Marketplace attribute*), 23
 - description (*connect.models.Param attribute*), 23

- description (*connect.models.UsageFile* attribute), 30
- deserialize() (*connect.models.BaseModel* class method), 15
- deserialize_json() (*connect.models.BaseModel* class method), 15
- detailed_description (*connect.models.Product* attribute), 24
- Directory (class in *connect.resources*), 33
- display_name (*connect.models.Item* attribute), 22
- distribution (*connect.models.ProductStatsInfo* attribute), 26
- Document (class in *connect.models*), 20
- documents (*connect.models.CustomerUiSettings* attribute), 20
- download_links (*connect.models.CustomerUiSettings* attribute), 20
- DownloadLink (class in *connect.models*), 20
- ## E
- email (*connect.models.Contact* attribute), 17
- email (*connect.models.User* attribute), 33
- end_time_utc (*connect.models.UsageRecord* attribute), 32
- enrolled (*connect.models.Contract* attribute), 18
- environment (*connect.models.TierConfigRequest* attribute), 29
- environment (*connect.models.UsageFile* attribute), 31
- equal() (*connect.rql.Query* method), 40
- error_code (*connect.models.ServerErrorResponse* attribute), 27
- error_details (*connect.models.UsageFile* attribute), 31
- errors (*connect.models.ServerErrorResponse* attribute), 27
- Event (class in *connect.models*), 20
- Events (class in *connect.models*), 20
- events (*connect.models.Asset* attribute), 13
- events (*connect.models.BillingRequest* attribute), 16
- events (*connect.models.Hub* attribute), 21
- events (*connect.models.Param* attribute), 23
- events (*connect.models.ProductConfigurationParameter* attribute), 26
- events (*connect.models.RecurringAsset* attribute), 26
- events (*connect.models.TierConfig* attribute), 28
- events (*connect.models.TierConfigRequest* attribute), 29
- events (*connect.models.UsageFile* attribute), 31
- events (*connect.resources.BillingRequest* attribute), 39
- events (*connect.resources.RecurringAsset* attribute), 39
- extension (*connect.models.PhoneNumber* attribute), 24
- external_id (*connect.models.Asset* attribute), 13
- external_id (*connect.models.ExtIdHub* attribute), 21
- external_id (*connect.models.RecurringAsset* attribute), 26
- external_id (*connect.models.UsageFile* attribute), 31
- external_id (*connect.resources.RecurringAsset* attribute), 39
- external_name (*connect.models.Asset* attribute), 13
- external_uid (*connect.models.Asset* attribute), 14
- external_uuid (*connect.models.RecurringAsset* attribute), 27
- external_uuid (*connect.resources.RecurringAsset* attribute), 39
- ExtIdHub (class in *connect.models*), 21
- ## F
- FailRequest, 9
- family (*connect.models.ProductCategory* attribute), 25
- FileCreationError, 9
- FileRetrievalError, 9
- filters() (*connect.resources.FulfillmentAutomation* method), 35
- filters() (*connect.resources.TierConfigAutomation* method), 37
- filters() (*connect.resources.UsageAutomation* method), 38
- filters() (*connect.resources.UsageFileAutomation* method), 38
- first_name (*connect.models.Contact* attribute), 17
- from_ (*connect.models.Renewal* attribute), 27
- Fulfillment (class in *connect.models*), 21
- FulfillmentAutomation (class in *connect.resources*), 34
- ## G
- get() (*connect.models.TierConfig* class method), 28
- get() (*connect.resources.TemplateResource* method), 36
- get_asset() (*connect.resources.Directory* method), 33
- get_conversation() (*connect.models.AssetRequest* method), 12
- get_instance() (*connect.config.Config* class method), 8
- get_item_by_global_id() (*connect.models.Asset* method), 14
- get_item_by_id() (*connect.models.Asset* method), 14
- get_item_by_mpn() (*connect.models.Asset* method), 14

get_marketplace() (*connect.resources.Directory method*), 34
 get_param_by_id() (*connect.models.Asset method*), 14
 get_param_by_id() (*connect.models.Configuration method*), 16
 get_param_by_id() (*connect.models.Item method*), 22
 get_param_by_id() (*connect.models.TierConfig method*), 29
 get_param_by_id() (*connect.models.TierConfigRequest method*), 30
 get_product() (*connect.resources.Directory method*), 34
 get_product_configurations() (*connect.models.Product method*), 24
 get_requests() (*connect.models.Asset method*), 14
 get_templates() (*connect.models.Product method*), 25
 get_tier_config() (*connect.resources.Directory method*), 34
 get_tier_config() (*connect.resources.FulfillmentAutomation method*), 36
 get_usage_template() (*connect.resources.UsageAutomation method*), 38
 getting_started (*connect.models.CustomerUiSettings attribute*), 20
 global_id (*connect.models.Item attribute*), 22
 greater() (*connect.rql.Query method*), 40
 greater_equal() (*connect.rql.Query method*), 40

H

hidden (*connect.models.Constraints attribute*), 17
 Hub (*class in connect.models*), 21
 hub (*connect.models.Connection attribute*), 17
 hub (*connect.models.ExtIdHub attribute*), 21
 HubInstance (*class in connect.models*), 21
 hubs (*connect.models.Marketplace attribute*), 23
 HubStats (*class in connect.models*), 21

I

icon (*connect.models.Country attribute*), 19
 icon (*connect.models.Marketplace attribute*), 23
 icon (*connect.models.Product attribute*), 25
 id (*connect.models.BaseModel attribute*), 15
 ilike() (*connect.rql.Query method*), 41
 in_() (*connect.rql.Query method*), 41
 inquired (*connect.models.Events attribute*), 20
 InquireRequest, 9
 instance (*connect.models.Hub attribute*), 21
 instance_id (*connect.models.Conversation attribute*), 19
 invalid (*connect.models.UsageRecords attribute*), 33
 Item (*class in connect.models*), 22
 item (*connect.models.BillingRequest attribute*), 16
 item (*connect.models.ProductConfigurationParameter attribute*), 26
 item (*connect.resources.BillingRequest attribute*), 39
 item_name (*connect.models.UsageRecord attribute*), 32
 item_npm (*connect.models.UsageRecord attribute*), 32
 item_precision (*connect.models.UsageRecord attribute*), 32
 item_search_criteria (*connect.models.UsageRecord attribute*), 32
 item_search_value (*connect.models.UsageRecord attribute*), 32
 item_type (*connect.models.Item attribute*), 22
 item_unit (*connect.models.UsageRecord attribute*), 32
 items (*connect.models.Asset attribute*), 14
 items (*connect.models.RecurringAsset attribute*), 27
 items (*connect.resources.RecurringAsset attribute*), 39

J

json (*connect.models.BaseModel attribute*), 15

L

label (*connect.models.ValueChoice attribute*), 33
 last_name (*connect.models.Contact attribute*), 17
 last_request (*connect.models.Company attribute*), 16
 last_request (*connect.models.Stat attribute*), 27
 LastRequest (*class in connect.models*), 22
 latest (*connect.models.Product attribute*), 25
 lesser() (*connect.rql.Query method*), 41
 lesser_equal() (*connect.rql.Query method*), 41
 like() (*connect.rql.Query method*), 41
 limit() (*connect.rql.Query method*), 42
 link (*connect.models.Activation attribute*), 10
 link (*connect.models.Agreement attribute*), 11
 list() (*connect.resources.TemplateResource method*), 36
 list_assets() (*connect.resources.Directory method*), 34
 list_marketplaces() (*connect.resources.Directory method*), 34
 list_products() (*connect.resources.Directory method*), 34
 list_tier_configs() (*connect.resources.Directory method*), 34
 listing (*connect.models.ProductStats attribute*), 26

M

Marketplace (class in *connect.models*), 22

marketplace (*connect.models.Agreement* attribute), 11

marketplace (*connect.models.Asset* attribute), 14

marketplace (*connect.models.AssetRequest* attribute), 12

marketplace (*connect.models.Contract* attribute), 18

marketplace (*connect.models.Param* attribute), 23

marketplace (*connect.models.ProductConfigurationParameter* attribute), 26

marketplace (*connect.models.RecurringAsset* attribute), 27

marketplace (*connect.models.TierConfig* attribute), 29

marketplace (*connect.models.TierConfigRequest* attribute), 30

marketplace (*connect.models.UsageFile* attribute), 31

marketplace (*connect.resources.RecurringAsset* attribute), 39

MarketplaceResource (class in *connect.resources*), 36

marketplaces (*connect.models.HubStats* attribute), 21

max_length (*connect.models.Constraints* attribute), 17

Message, 9

message (*connect.exceptions.Message* attribute), 9

message (*connect.models.Activation* attribute), 10

messages (*connect.models.Conversation* attribute), 19

min_length (*connect.models.Constraints* attribute), 17

model_class (*connect.resources.AssetRequestResource* attribute), 40

model_class (*connect.resources.FulfillmentAutomation* attribute), 36

model_class (*connect.resources.MarketplaceResource* attribute), 36

model_class (*connect.resources.TierConfigAutomation* attribute), 37

model_class (*connect.resources.UsageAutomation* attribute), 38

model_class (*connect.resources.UsageFileAutomation* attribute), 39

month (*connect.models.Anniversary* attribute), 11

mpn (*connect.models.Item* attribute), 22

N

name (*connect.models.Agreement* attribute), 11

name (*connect.models.Company* attribute), 16

name (*connect.models.Contract* attribute), 18

name (*connect.models.Country* attribute), 19

name (*connect.models.Hub* attribute), 21

name (*connect.models.Item* attribute), 22

name (*connect.models.Marketplace* attribute), 23

name (*connect.models.Param* attribute), 23

name (*connect.models.Product* attribute), 25

name (*connect.models.ProductCategory* attribute), 25

name (*connect.models.ProductFamily* attribute), 26

name (*connect.models.Template* attribute), 28

name (*connect.models.TierConfig* attribute), 29

name (*connect.models.UsageFile* attribute), 31

name (*connect.models.User* attribute), 33

needs_migration() (*connect.models.AssetRequest* method), 12

new_items (*connect.models.AssetRequest* attribute), 12

next_date (*connect.models.Billing* attribute), 15

not_equal() (*connect.rql.Query* method), 42

note (*connect.models.AssetRequest* attribute), 12

note (*connect.models.UsageFile* attribute), 31

notes (*connect.models.TierConfigRequest* attribute), 30

O

obj (*connect.exceptions.Message* attribute), 9

offset() (*connect.rql.Query* method), 42

old_quantity (*connect.models.Item* attribute), 22

open_request (*connect.models.TierConfig* attribute), 29

order_by() (*connect.rql.Query* method), 42

ordering() (*connect.rql.Query* method), 42

out() (*connect.rql.Query* method), 42

owner (*connect.models.Agreement* attribute), 11

owner (*connect.models.Contract* attribute), 18

owner (*connect.models.Marketplace* attribute), 23

owner (*connect.models.Product* attribute), 25

P

Param (class in *connect.models*), 23

parameter (*connect.models.ProductConfigurationParameter* attribute), 26

params (*connect.exceptions.InquireRequest* attribute), 9

params (*connect.models.Asset* attribute), 14

params (*connect.models.Configuration* attribute), 16

params (*connect.models.Item* attribute), 22

params (*connect.models.RecurringAsset* attribute), 27

params (*connect.models.ServerErrorResponse* attribute), 27

params (*connect.models.TierConfig* attribute), 29

params (*connect.models.TierConfigRequest* attribute), 30

params (*connect.resources.RecurringAsset* attribute), 39

params_form_url (*connect.models.AssetRequest* attribute), 12

parent (*connect.models.Agreement* attribute), 11

parent (*connect.models.ProductCategory* attribute), 25

parent_configuration (connect.models.TierConfigRequest attribute), 30

pending (connect.models.Events attribute), 20

pending (connect.models.UsageStats attribute), 33

Period (class in connect.models), 24

period (connect.models.Billing attribute), 15

period (connect.models.BillingRequest attribute), 16

period (connect.models.Item attribute), 22

period (connect.resources.BillingRequest attribute), 39

period_delta (connect.models.Renewal attribute), 27

period_from (connect.models.Period attribute), 24

period_from (connect.models.UsageFile attribute), 31

period_to (connect.models.Period attribute), 24

period_to (connect.models.UsageFile attribute), 31

period_uom (connect.models.Renewal attribute), 27

phase (connect.models.Param attribute), 23

phone_number (connect.models.Contact attribute), 17

phone_number (connect.models.PhoneNumber attribute), 24

PhoneNumber (class in connect.models), 24

postal_code (connect.models.ContactInfo attribute), 18

processed_file_uri (connect.models.UsageFile attribute), 31

Product (class in connect.models), 24

product (connect.models.Asset attribute), 14

product (connect.models.Connection attribute), 17

product (connect.models.RecurringAsset attribute), 27

product (connect.models.TierConfig attribute), 29

product (connect.models.TierConfigRequest attribute), 30

product (connect.models.UsageFile attribute), 31

product (connect.models.UsageListing attribute), 32

product (connect.resources.RecurringAsset attribute), 39

ProductCategory (class in connect.models), 25

ProductConfiguration (class in connect.models), 25

ProductConfigurationParameter (class in connect.models), 25

ProductFamily (class in connect.models), 26

products (connect.config.Config attribute), 8

ProductStats (class in connect.models), 26

ProductStatsInfo (class in connect.models), 26

provider (connect.models.Attributes attribute), 15

provider (connect.models.Connection attribute), 17

provider (connect.models.Stats attribute), 27

provider (connect.models.UsageFile attribute), 31

provider (connect.models.UsageListing attribute), 32

published_at (connect.models.Product attribute), 25

Q

quantity (connect.models.Item attribute), 22

quantity (connect.models.UsageRecord attribute), 32

Query (class in connect.rql), 40

R

reason (connect.models.AssetRequest attribute), 12

reason (connect.models.TierConfigRequest attribute), 30

reconciliation (connect.models.Constraints attribute), 17

reconciliation (connect.models.Param attribute), 23

records (connect.models.UsageFile attribute), 31

RecurringAsset (class in connect.models), 26

RecurringAsset (class in connect.resources), 39

rejected (connect.models.Events attribute), 21

rejection_note (connect.models.UsageFile attribute), 31

RejectUsageFile, 9

removed_items (connect.models.AssetRequest attribute), 12

render () (connect.resources.TemplateResource method), 36

Renewal (class in connect.models), 27

renewal (connect.models.Item attribute), 22

representation (connect.models.Template attribute), 28

required (connect.models.Constraints attribute), 17

requires_reseller_information (connect.models.ProductConfiguration attribute), 25

S

schema (connect.models.UsageFile attribute), 31

scope (connect.models.Param attribute), 23

select () (connect.rql.Query method), 42

ServerError, 9

ServerErrorResponse (class in connect.models), 27

short_description (connect.models.Product attribute), 25

signee (connect.models.Contract attribute), 18

SkipRequest, 9

sourcing (connect.models.Marketplace attribute), 23

sourcing (connect.models.ProductStatsInfo attribute), 26

start_time_utc (connect.models.UsageRecord attribute), 32

Stat (class in connect.models), 27

state (connect.models.ContactInfo attribute), 18

Stats (class in connect.models), 27

stats (connect.models.Agreement attribute), 11

stats (connect.models.Billing attribute), 16

stats (*connect.models.Hub* attribute), 21
 stats (*connect.models.Product* attribute), 25
 stats (*connect.models.UsageFile* attribute), 31
 status (*connect.models.Asset* attribute), 14
 status (*connect.models.AssetRequest* attribute), 12
 status (*connect.models.Connection* attribute), 17
 status (*connect.models.Contract* attribute), 18
 status (*connect.models.Product* attribute), 25
 status (*connect.models.RecurringAsset* attribute), 27
 status (*connect.models.TierConfig* attribute), 29
 status (*connect.models.TierConfigRequest* attribute), 30
 status (*connect.models.UsageFile* attribute), 31
 status (*connect.models.UsageListing* attribute), 32
 status (*connect.resources.RecurringAsset* attribute), 39
 submit_usage () (*connect.resources.UsageAutomation* method), 38
 submitted (*connect.models.Events* attribute), 21
 SubmitUsageFile, 10
 suspend_resume_supported (*connect.models.ProductConfiguration* attribute), 25

T

Template (*class in connect.models*), 28
 template (*connect.models.TierConfig* attribute), 29
 template (*connect.models.TierConfigRequest* attribute), 30
 TemplateResource (*class in connect.resources*), 36
 text (*connect.models.ConversationMessage* attribute), 19
 tier (*connect.models.UsageRecord* attribute), 32
 tier1 (*connect.models.TierAccounts* attribute), 28
 tier2 (*connect.models.TierAccounts* attribute), 28
 tier_level (*connect.models.TierConfig* attribute), 29
 tier_level (*connect.models.TierConfigRequest* attribute), 30
 TierAccount (*class in connect.models*), 28
 TierAccountRequest (*class in connect.models*), 28
 TierAccounts (*class in connect.models*), 28
 TierConfig (*class in connect.models*), 28
 TierConfigAutomation (*class in connect.resources*), 37
 TierConfigRequest (*class in connect.models*), 29
 tiers (*connect.models.Asset* attribute), 15
 tiers (*connect.models.RecurringAsset* attribute), 27
 tiers (*connect.models.TierConfigRequest* attribute), 30
 tiers (*connect.resources.RecurringAsset* attribute), 39
 title (*connect.models.Agreement* attribute), 11
 title (*connect.models.Document* attribute), 20
 title (*connect.models.DownloadLink* attribute), 20
 title (*connect.models.Param* attribute), 23

to (*connect.models.Renewal* attribute), 27
 topic (*connect.models.Conversation* attribute), 19
 type (*connect.models.Agreement* attribute), 11
 type (*connect.models.AssetRequest* attribute), 13
 type (*connect.models.BillingRequest* attribute), 16
 type (*connect.models.Connection* attribute), 17
 type (*connect.models.Contract* attribute), 18
 type (*connect.models.HubInstance* attribute), 21
 type (*connect.models.Item* attribute), 22
 type (*connect.models.LastRequest* attribute), 22
 type (*connect.models.Param* attribute), 23
 type (*connect.models.TierConfigRequest* attribute), 30
 type (*connect.resources.BillingRequest* attribute), 39

U

unique (*connect.models.Constraints* attribute), 17
 uom (*connect.models.Period* attribute), 24
 update_param_asset_request () (*connect.resources.AssetRequestResource* method), 40
 update_parameters () (*connect.resources.FulfillmentAutomation* method), 36
 update_parameters () (*connect.resources.TierConfigAutomation* method), 37
 updated (*connect.models.Agreement* attribute), 11
 updated (*connect.models.AssetRequest* attribute), 13
 updated (*connect.models.Contract* attribute), 18
 updated (*connect.models.Events* attribute), 21
 uploaded (*connect.models.Events* attribute), 21
 uploaded (*connect.models.UsageStats* attribute), 33
 url (*connect.models.Document* attribute), 20
 url (*connect.models.DownloadLink* attribute), 20
 usage_file_uri (*connect.models.UsageFile* attribute), 31
 usage_record_id (*connect.models.UsageRecord* attribute), 33
 usage_record_note (*connect.models.UsageRecord* attribute), 33
 UsageAutomation (*class in connect.resources*), 38
 UsageFile (*class in connect.models*), 30
 UsageFileAction, 10
 UsageFileAutomation (*class in connect.resources*), 38
 UsageListing (*class in connect.models*), 31
 UsageRecord (*class in connect.models*), 32
 UsageRecords (*class in connect.models*), 33
 UsageStats (*class in connect.models*), 33
 User (*class in connect.models*), 33

V

valid (*connect.models.UsageRecords* attribute), 33
 validated (*connect.models.Events* attribute), 21

validated (*connect.models.UsageStats* attribute), 33
value (*connect.models.Param* attribute), 23
value (*connect.models.ProductConfigurationParameter* attribute), 26
value (*connect.models.ValueChoice* attribute), 33
value_choice (*connect.models.Param* attribute), 23
value_choices (*connect.models.Param* attribute), 23
value_error (*connect.models.Param* attribute), 24
ValueChoice (*class in connect.models*), 33
vendor (*connect.models.Attributes* attribute), 15
vendor (*connect.models.Connection* attribute), 17
vendor (*connect.models.Stats* attribute), 28
vendor (*connect.models.UsageFile* attribute), 31
vendor (*connect.models.UsageListing* attribute), 32
version (*connect.models.Agreement* attribute), 11
version (*connect.models.Contract* attribute), 18
version (*connect.models.Product* attribute), 25
version_contracts (*connect.models.Agreement* attribute), 11
version_created (*connect.models.Agreement* attribute), 11
version_created (*connect.models.Contract* attribute), 19
versions (*connect.models.AgreementStats* attribute), 11
visible_for (*connect.models.DownloadLink* attribute), 20

Z

zone (*connect.models.Country* attribute), 19
zone (*connect.models.Marketplace* attribute), 23